Kansas Permit No.: M-AR64-SU01

Federal Permit No.: KSR410024

KANSAS WATER POLLUTION CONTROL MUNICIPAL SEPARATE STORM SEWER SYSTEM (MS4) PERMIT AND AUTHORIZATION TO DISCHARGE UNDER THE NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM

Pursuant to the provisions of Kansas Statutes Annotated 65-164 and 65-165, the Federal Water Pollution Control Act as amended, 33 U.S.C. 1251 et seq., the "Act",

Permittee:

Mulvane, City of

Permittee's Address:

211 North 2nd Street Mulvane, KS 67110

Drainage Basin:

Lower Arkansas River

County:

Sedgwick

is hereby authorized to discharge stormwater from the municipal separate storm sewer system (MS4) as described herein in accordance with the limitations, conditions and requirements set forth in this permit.

This permit is effective December 1, 2019, supersedes the previously issued MS4 general permit M-AR64-SU01 and expires November 30, 2024.

PERMIT AREA AND AUTHORIZED DISCHARGES

This permit covers all areas within the permittee's MS4 jurisdiction which are also located in the urbanized area as defined by the 2010 U.S. Census (the Permit Area). The Permit Area may change based upon areas incorporated into or removed from the permittee's jurisdictional area during the term of this permit.

This permit authorizes the discharge of all existing or new stormwater point source discharges from the Municipal Separate Storm Sewer System (MS4) located within the Permit Area. New stormwater discharges are those which are created and/or incorporated into the permittee's MS4 during the term of this permit.

Lea. noma mo

Secretary, Kansas Department of Health and Environment

November 27, 2019

Date

Kansas Permit No.: M-AR64-SU01

Page 2 of 57

PART I. STORMWATER MANAGEMENT PROGRAM (SMP) DOCUMENT REQUIREMENTS

A. Current Stormwater Management Program

The permittee shall continue to implement and enforce the current Stormwater Management Program (SMP), as documented in the SMP document, until an updated SMP is implemented. Revised or modified surface water monitoring may be implemented in 2019 as allowed and if so required by this permit.

Any updated SMP shall be designed to:

- 1. Reduce the discharge of pollutants from the municipal separate storm sewer system (MS4) to the Maximum Extent Practicable (MEP),
- 2. Continue to implement the six minimum control measures as listed in PART I Section C,
- 3. Satisfy the requirements of this permit, the Clean Water Act and Kansas surface water quality statutes and regulations.

Implementation of Best Management Practices (BMPs) consistent with the provisions of the SMP document and this permit constitutes compliance with the standard of reducing pollutants to the Maximum Extent Practicable.

B. Updated Stormwater Management Program document

The SMP shall be updated and submitted to KDHE between January 1 and February 28 of 2021 (submitted with the Annual Report and the updated SMP must be effective in 2021). As this permit imposes additional requirements for implementation of BMPs and/or surface water monitoring [see PART II. Total Maximum Daily Load (TMDL) Best Management Practices and Surface Water Monitoring] beyond what the previous permit imposed, the current SMP shall be modified with the SMP document updated to include the additional requirements imposed by this permit. Some specific requirements for updating the SMP document are addressed in PART I Section D. "Total Maximum Daily Load (TMDL) Regulated Pollutants." Additionally, to comply with new EPA regulations [National Pollutant Discharge Elimination System (NPDES) Municipal Separate Storm Sewer System General Permit Remand Rule (Remand Rule)], as finalized and effective January 9, 2017, this permit must include requirements in clear, specific, and measurable terms. Tables of BMPs are listed along with point values, and the permittee must implement sufficient listed BMPs to achieve minimum point requirements for each year beginning in 2021. The Remand Rule was published on December 9, 2016 in the Federal Register, Vol. 81, No. 237 beginning on page 89320.

This rule clarifies that terms and conditions must be expressed in terms which are "clear, specific, and measurable." The permit requirements must be enforceable and must provide a set of performance expectations and schedules readily understood by the permittee, the public, and the permitting authority alike. To provide as much flexibility to the permittee in implementing their stormwater management program in compliance with this permit and the Remand Rule, KDHE has elected to establish a point system and a list of various BMPs, tasks, or other conditions with associated point values to be tallied and demonstrate compliance with the total point requirement for each of the Six Minimum Control Measures and TMDL BMPs when required.

Kansas Permit No.: M-AR64-SU01 Page 3 of 57

Modification of the SMP is permitted as the need arises. Modifications can be accomplished with any of the following methods:

- 1. Normally the SMP document is updated near the end of the calendar year and submitted to KDHE for review along with the annual report which is due after the first of the calendar year but before the 28th of February. In this case the permittee can begin implementation of the new SMP as soon as they have submitted the SMP to KDHE. The permittee is required to implement the SMP, which was most recently submitted to KDHE along with the annual report, throughout the entire year and may continue to implement the updated SMP until subsequently modified. The updated SMP as submitted must be approved by KDHE. If KDHE finds the SMP is not approvable, requirements for modification and resubmittal will be addressed to the permittee.
- 2. If it becomes necessary to modify the SMP at some time other than when the annual report is submitted to KDHE, the permittee may make the modifications to the SMP document and submit the SMP document to KDHE for approval. The permittee shall not begin implementation of the modified SMP until after KDHE has provided approval. KDHE may provide full approval of the modified SMP, or may provide conditional approval, may require revision of the modified SMP document and resubmission for subsequent review or may elect to not approve the modified SMP.
- 3. KDHE may require the permittee modify the SMP at any time, requirements for modification and resubmittal will be addressed to the permittee

C. Six Minimum Control Measures

The Permittee shall continue to review, update and implement BMPs with measurable goals for each of the six minimum control measures. The six minimum control measures and requirements are as follows:

1. Public Education and Outreach

The permittee shall continue to implement a public education program which includes distribution of educational materials to the community or conducting equivalent outreach activities which address the impacts of stormwater discharges on water bodies and the steps the public can take to reduce pollutants in stormwater runoff.

a. The implementation of BMPs for this minimum control measure must result in accumulation of a minimum of 4 points total on an annual basis for each calendar year 2021 and 2022. The point total requirement increases to 7 points for each calendar year beginning in 2023. The following table lists various BMPs, measurable goals, and the required timing-period or implementation-schedule to qualify for the points in the year.

In cases where the permittee is already implementing a BMP which qualifies for points, they may continue implementation of the BMP and earn the listed points as allowed for the first year of implementation under this permit as well as subsequent years.

Multiple BMPs involve holding public hearings or public forums; a single public hearing or forum can be held which addresses multiple topics and points claimed for all of the multiple BMPs implemented.

In addition to implementing a Public Education and Outreach program as required above, the permittee must implement sufficient listed BMPs in the table below to qualify for the required number of points.

BMP Summary	Measurable Goal	Implementation Time Schedule etc.	Points
Lbmp P Ed & O - 01 Maintain a stormwater webpage for the permittee.	Maintain the webpage with up to date information with all links effective and valid information. Check all links and update website as necessary on a minimum monthly basis. Document monthly checks in log book and indicate changes with logged summaries.	The webpage must be available throughout the year once it is posted and initially made available. In the initial year posted it must be available for a minimum of 3 months to qualify for the points. In subsequent calendar years the points may be claimed if	3 points may be claimed in the first year implemented, and 2 points may be claimed for each successive year the webpage is maintained available.
Lbmp P Ed & O - 02		the webpage has been maintained throughout the twelve months.	
Distribute educational materials (either flyers, brochures, catalog mailings, handouts, or e-mails) addressing various pertinent stormwater public education topics.	Number of all flyers, brochures, catalog mailings, handouts, or e-mails distributed in a year shall equal or exceed the most recent U.S. Census Bureau decennial housing units value for the permit area. The applicable U.S. Census housing units value shall be documented, and the number of flyers, brochures, or e-mails distributed shall also be documented. This information and copies of the flyers, brochures, or e-mails shall be retained on file.	Either flyers, brochures, catalog mailings, handouts, or e-mails are to be distributed in at least two separate batches, ideally in separate seasons (either winter, spring, summer or fall). However, the required number of flyers, brochures, or e-mails must be distributed in a single calendar year and the points can be claimed for that year.	2 points may be claimed in a year in which the required number of flyers, brochures, catalog mailings, handouts, or e-mails are distributed.
Provide either training or educational materials to permittee identified businesses at high risk of contributing to stormwater pollution.	Training or educational materials must be provided, within the year, to at least five separate businesses	The required amount of training or distribution of educational materials must occur within the	2 points may be claimed in any year in which the required amount of training or distribution of educational

Such businesses can	if the population of	year for which	material
include, but are not	the municipality is	points are claimed.	occurs.
limited to, food	greater than 10,000,	-	
service, auto service,	or three businesses		
disaster response and	if the population of		
janitorial services. The	the municipality is		
training or educational	between 3,000 and		
materials shall address	9,999, or two		
best management	separate businesses		
practices they can	if the population of		
employ to minimize or	the municipality is		
avoid adverse stormwater	less than 3,000.	1	
impacts due to their	1000 011011 07000.	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
operations.	There is no		
operations.	requirement to		
•	provide training to		
	business in separate		
	business categories,		
	although it is		
	allowed.		
Lbmp P Ed & 0 - 04	and the same of th		
			2 points may
			be claimed in
Apply notification,	Apply this	The required number	years when the
placard, covers/hatches	notification on at	of placards,	required
with message, or	least 10% of all	covers/hatches with	number of
stencil, on stormwater	known stormwater	message, or	inlets (10%)
inlets to provide a	inlets in the MS4.	stencils must be	receive
message similar to "No		placed within the	placards,
Dumping - Drains to		year for which	covers/hatches
River"		points are claimed.	with message,
		Alternately, points	or stencils or
		may be claimed in	in subsequent
		any subsequent year	years when an
		when an additional	additional 5%
		5% of all known	of all known
		stormwater inlets	stormwater
		in the MS4 bear the	inlets in the
		placard,	MS4 bear the
		covers/hatches with	placard,
		message, or	covers/hatches
		stencil.	with message,
			or stencil.
Lbmp P Ed & 0 - 05			
Post the municipality's	The two documents	Months for which	1 point may be
MS4 permit and SMP	must be posted for at	,	claimed for
document on either the	least six months of	the posting occurs must be within the	posting each
stormwater web page or			year (minimum
the municipal webpage.	the year to claim one	year for which	of at least
the municipal webpage.	point.	points are claimed.	six months).
		No "carryover" of	
		months from one year to the next.	
Lbmp P Ed & 0 - 06		Jear to the next.	2 points may
			be claimed
			for each year
Provide either a	Respond to all	The	the hotline /
stormwater telephone	reported complaints	hotline/reporting	reporting
hotline or web based or	within 10 days and,	system must be	system is
	1-3	1 - 1 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 -	T shorem re

maintained and

available to the

public reporting of resolve or establish public for at least available. An illicit discharges. a schedule for six months in the additional resolution within 20 year to claim the point may be days. Actual points. claimed for resolution may take each illicit more than 20 days, discharge but the schedule for resolved in resolution must be the year up to finalized and the a limit of 2 efforts to implement additional resolution must begin points per within 20 days year. One following receipt of point allowed complaint. Document per illicit complaints and discharge response/resolution resolved. process for all complaints received in the year. Resolution of an illicit discharge can include, but is not limited to: elimination of the discharge; on-site treatment to allow discharge to the MS4 (normally requires an NPDES permit); redirecting the discharge to a location that the discharge is not considered illicit, i.e., sanitary sewer or to holding tanks to allow the waste to be hauled off for appropriate treatment, reuse/recycle or disposal. Lbmp P Ed & O - 07 Provide educational Identify and educate All the 3 points may material annually to at at least 4 requirements for be claimed least four groups, groups/entities from sending educational each year this including each of the the listed types material to the BMP is following types: annually developing various groups must implemented in Residents, topics that are group occur in a single compliance Businesses/Institutions, specific and address year to qualify for with the activities and or Commercial the points in that specified entities/Developers, and pollutants of year. requirements. Industrial facilities. concern. The educational material ALL DOT may be provided as any of the following:

if found valid,

text message method for

Kansas Permit No.: M-AR64-SU01 Page 7 of 57

		 	
> Brochures > Flyers > E-mails > Press release Lbmp P Ed & O - 08 Provide stormwater	Provide or fund an	All of the required	
education for students at a school campus within K-12 (those grades present at the campus) within the permittee's jurisdiction or within 30 miles from this permit area. The training may be limited to the individual campus (local school buildings associated with a single address). This training does not need to be provided to the entire school system, e.g., USD. Alternately, funding stormwater BMP installations and/or field trips at the school campus will qualify.	educator or speaker that will reach at least 5% of the K-12 students as normally attend school in the selected school campus. Alternately, the funding of BMPs at the school campus may provide for any of the following: > Installation of BMPs at the school > stormwater related field trips > water quality stream sampling activities > construction of rain gardens on school property > rain barrel workshops > rain garden workshops	students (5% minimum) in K-12 at the selected campus must be educated in a single year to qualify for the points in that year. Alternately, stormwater BMPs may be funded at a school campus where students may participate in installation or observe operation of the BMPs. Any of the items listed under measurable goals qualify.	3 points may be claimed each year this BMP is implemented in compliance with the specified requirements (provide education and/or fund stormwater BMP installations at the school campus).
1. Operate an information booth at a large public event, (such as a sports event, fair, or music festival) where at least an estimated 1,000 or more individuals attend.		All events shall have the booth staffed by the permittee for at least 50% of the days the event occurs.	2 points may be claimed each year this BMP is implemented in compliance with the specified requirements for alternative 1. (1,000 or more attendees) or alternative 2. (3,000
2. Alternately, operate an information booth			attendees).

at multiple public events, (such as a sports event, fair, or music festival) where a cumulative estimated total of 3,000 or more individuals attend. 3. And finally, a single point can be claimed for operating an information both at a public event where at least an estimated 200 or		The state of the	The state of the s
more individuals attend.			
Lbmp P Ed & O - 10			
Provide either training or educational materials to lawn/turf care service entities addressing best management practices they can employ to minimize or avoid adverse stormwater impacts due to their operations.	Training or educational materials must be provided, within the year, to at least five lawn/turf care service entities or at least 20% of the lawn care service entities located in the municipality whichever is least.	The required amount of training or distribution of educational materials must occur within the year for which points are claimed.	2 points may be claimed in any year in which the required amount of training or distribution of educational material occurs.
	Install and/or maintain signs to discourage littering. Signs are to be located in areas where littering has been a problem.	Credit can be claimed for any year in which signs are installed and in place for greater than six months or in cases where signs have previously been installed in any year where the signs remain posted for the full year.	l point may be claimed for the year when signs are posted for six months or more, or 1 point may be claimed in subsequent years where the signs remain posted throughout the year.
Lbmp P Ed & O - 12 Create a stormwater information brochure to provide to the public at	Have multiple copies of the brochure available during at least 10 meetings or	The brochures shall address stormwater topics of concern.	1 point may be claimed in any year the brochures are made available to the public at meetings

public meetings and/or hearings	hearings open to the public during the year. Provide the brochures to the public at no charge.		and/or hearings as required.
Lbmp P Ed & O - 13			
Operate an adopt a highway program to utilize public volunteers to clean road right-of-way.	The volunteers shall clean at least a two-mile segment of road either within the permit area or adjacent to the permit area. Alternately multiple spots (such as roadways, parks, and waterways) which are cleaned and equate to or exceed a two-mile road clean-up can qualify for a point.	The road right-of- way shall be cleaned at least once per year. Points may be claimed for any year in which cleaning has occurred.	l point may be claimed in any year a two-mile road segment is cleaned or alternately multiple spots are cleaned which equate to or exceed a two-mile road clean-up.
Lbmp P Ed & 0 - 14			
Hold a media campaign addressing various pertinent stormwater public education topics.	Estimated media exposure during prime-time broadcasting for the duration of the campaign shall be 10 times the most recent U.S. Census Bureau decennial population value for the permit area. The date, time, and estimated media exposure for each spot broadcast shall be documented and kept on file along with the applicable U.S. Census population value.	The media campaign shall be run within the year for which points are claimed. A new media campaign shall be run for each year points are claimed.	2 points may be claimed in a year in which the media campaign meeting the minimum exposure rate is conducted.
Lbmp P Ed & 0 - 15			8
Develop or participate in an ongoing social media program on pertinent stormwater public education topics.	Publish or share social media content on the permittee's social media accounts at least six times per year. Record post topic, the number of impressions and engagement for each post. Include link to permittee's	The required number of social media posts must occur within the year for which the posts are claimed.	2 points can be claimed in a year which the required number of content is shared.

	stormwater education website.		101
Ibmp P Ed & O - 16 Operate an information booth at a public event or hold a public event which is intended to improve public understanding of issues related to water quality. The event may be associated with any	At least an estimated 800 or more individuals must attend the event.	The booth must be staffed at least 50% of the time the event is open to the public.	2 points may be claimed each year this BMP is implemented in compliance with the specified requirements. Municipal staff from
environmental related issue including but not limited to an environmental expo, earth day, world wetlands day, international day of action for rivers, world fish migration day, world biodiversity day, world oceans day, world cleanup day, world water monitoring day, world rivers day, and America recycles day.			multiple permittees may staff the both and claim points, for their municipality, for this BMP if their staff meet the 50% of the time staffing requirement.
Lbmp P Ed & O - 17		ikum —	
Operate an adopt a street program to utilize public volunteers to clean street right-of-way.	The volunteers shall clean at least a two-mile segment of street, either a single street or multiple streets, either within the permit area or adjacent to the permit area.	The street right- of-way shall be cleaned at least once per year. Points may be claimed for any year in which cleaning has occurred.	1 point may be claimed in any year at least two miles of street right-of-way is cleaned by volunteers.

- b. Documentation of compliance with the goal and implementation time schedule must be maintained on file to claim the associated points. Permittee is responsible for implementing adequate BMPs to comply with the Public Education and Outreach requirements of this permit and be able to claim at least the required number of points in the calendar years as specified above. Extent of compliance, i.e., equal or exceed the required annual point total or failure to reach the required annual point total, must be reported in the Annual Report.
- c. The permittee is not limited to implementation of the BMPs listed in the above table. Several other BMPs may be implemented, however, only implementation of the BMPs listed in the table may be documented and counted toward the required annual point total.

Kansas Permit No.: M-AR64-SU01 Page 11 of 57

2. Public Involvement/Participation

The permittee shall continue to implement a public involvement and participation program to solicit public comments and recommendations regarding the BMPs and measurable goals utilized by the permittee to comply with the permit. The permittee shall comply with State and local public notice requirements when implementing a public involvement and participation program.

a. The implementation of BMPs for this minimum control measure must result in accumulation of a minimum of 3 points total on an annual basis for each calendar year 2021 and 2022. The point total requirement increases to 6 points for each calendar year beginning in 2023. The following table lists various BMPs, measurable goals, and the required timing-period or implementation-schedule to qualify for the points in the year.

In cases where the permittee is already implementing a BMP which qualifies for points, they may continue implementation of the BMP and earn the listed points as allowed for the first year of implementation under this permit as well as subsequent years.

Multiple BMPs involve holding public hearings or public forums; a single public hearing or public forums can be held which addresses multiple topics and points claimed for all of the multiple BMPs implemented.

In addition to implementing a Public Involvement/Participation program as required above, the permittee must implement sufficient listed BMPs in the table below to qualify for the required number of points.

BMP Summary	Measurable Goal	Implementation Time Schedule etc.	Points
Lbmp P I/P - 01			
Hold a public hearing or public forum to notify the public about stormwater program activities and to solicit public comments regarding stormwater issues.	Provide public notice of the hearing/forum, invite local news media, either newspaper, radio or TV, and document the hearing with attendance sign-in sheet and minutes of the hearing which include public comments and responses.	Retain copies of the notices to public, invitations to attend, attendance sign-in sheets, and minutes. Points may be claimed in year which hearing is held.	2 points may be claimed each year this BMP is implemented in compliance with the specified requirements.
Lbmp P I/P - 02 Establish a citizens advisory committee.	Host the citizens advisory committee meetings twice yearly and receive comments and guidance from the committee regarding the SMP. Retain on file copies of the attendance list and minutes of the meetings.	The citizens advisory committee must hold at least two meetings in the year which points are claimed.	3 points may be claimed each year this BMP is implemented in compliance with the specified requirements.

			Page 12 of 5
Lbmp P I/P - 03			
Hold park or stream bank clean-up events for public volunteers to aid municipal staff in removing trash, debris, or pollutant sources from the selected clean-up area.	Clean an area which must be equal to or greater than one acre or alternately at least 200 yards of streambank. Alternately, for municipalities with less than 500 population clean an area which must be equal to or greater than a quarter of an acre or alternately at least 100 feet of streambank.	At least one such clean-up activity must occur in the year for which points are claimed.	3 points may be claimed each year this BMP is implemented in compliance with the specified requirements.
Lbmp P I/P - 04			
Train either citizen watch groups, homeowner associations (HOAs), or public service groups to recognize illicit discharge activities and communicate observations to appropriate municipal staff.	Provide training or distribute training materials to the group participants at least once annually.	At least one such training activity or distribution of training materials must be provided to the group in the year for which points are claimed.	2 points may be claimed each year this BMP is implemented in compliance with the specified requirements.
Lbmp P I/P - 05			
Provide at least two events for residents to engage in cleanup activities and improve water quality in the municipality.	Provide at least two events in streams, streamside parks, areas adjacent to public waterways, and/or other green infrastructure/water resources. These events can be any of the following: Environmental restoration events, stream cleanups, tree plantings, or stream monitoring.	At least two events in compliance with the stated goals must be conducted within the year for which points are claimed.	3 points may be claimed each year this BMP is implemented in compliance with the specified requirements.
Lbmp P I/P - 06			2 points may
Establish a program to encourage residents to install stormwater	Encouragement can include funding, grants, and other	One or more of the listed methods of encouragement must	be claimed each year this BMP is implemented in compliance

			
treatment best management practices on their property.	financial incentives, trainings and or giveaways. Stormwater treatment BMPs can include: rain barrels, rain gardens, native plantings, native trees, cisterns and vegetated swales. Record participation numbers annually.	be implemented in the year for which points are claimed.	with the specified requirements, with the addition of 1 additional point (for a total of 3 points in the year) each year that participation increases 10% from the previous year.
Enact either an ordinance, a resolution, or other enforceable requirement that requires pet owners or their keepers to immediately and properly dispose of their pet's solid waste deposited at parks or rest areas owned by the permittee.	The ordinance or resolution or other enforceable measure shall be enacted, and signs posted informing the public of their obligation at the park. The installation of a pet waste bag dispenser in the public area qualifies as adequate signage.	In the year the Measurable Goal requirement is implemented the point may be claimed and for each year thereafter.	l point may be claimed for the year in which the Measurable Goal requirements are enacted, and l points may be claimed for each subsequent year the Measurable Goal requirements remain in effect.
Lbmp P I/P - 08 Provide a monetary donation to a scholarship fund for students pursuing a degree in an environmental program which would qualify them to work in a field which can result in water pollution control.	A \$500 contribution in a year is the minimum acceptable amount to achieve this goal.	The donation must be made in the year the points are claimed.	2 points may be claimed each year this BMP goal is achieved.
Lbmp P I/P - 09 Distribute stormwater educational materials to the public within this permit area. Alternately, the permittee may provide	The educational materials, for each topic, which are distributed or supplied must have a value of at least \$50. Topics may be anything related to	For educational materials distributed or provided to nearby municipalities each year points may be claimed	1 point may be claimed per topic addressed in compliance with the requirements, up to a total of 5 points/topics.

stormwater educational	stormwater including	when materials are	
materials, e.g.	but not limited to	provided with	34114 5
brochures, flyers, or	clean-up guidance	equal or greater	The state of the s
pamphlets. These	following flooding,	value as required	4 1 1 1 1 1 1 1 1 1 1 1 1
materials may address	discouraging littering,	for each separate	
various stormwater	explaining and	topic.	
topics. For this	discouraging illicit	J J J J J J J J J J J J J J J J J J J	
alternative these	discharges to the storm		
materials may be	sewers, guidance on		
provided to other	constructed BMPs for		
nearby municipalities	home owners (rain		
for distribution to	gardens, rain barrels,		10.00
the public. The			
nearby municipalities	etc.) guidance on area household hazardous		
must be within 30			
	waste receiving		11.00
miles from this permit	centers, and guidance		
area.	on area recycling	The state of the s	San
	programs.		
Lbmp P I/P - 10			
Establish a program to	The intern must receive	The internship	
employ (either paid or	the same environmental	must last at least	
unpaid) high school or	related training a new	8 weeks in the	
college age	full-time employee	year when points	2 points may
environmental interns	would receive, within	are claimed.	be claimed
in an environmental	the first six months of	are craimed.	each year this
related program	the full-time		BMP goal is
including but not	employee's employment,		achieved per
limited to either the	during their		intern.
wastewater utility,	internship.		
stormwater utility,	THEFTHOUTD.		
potable water utility			
or solid waste			
utility.			

- b. Documentation of compliance with the goal and implementation time schedule must be maintained on file to claim the associated points. Permittee is responsible for implementing adequate BMPs to comply with the Public Involvement/Participation requirements of this permit and be able to claim at least the required number of points in the calendar years as specified above. Extent of compliance, i.e., equal or exceed the required annual point total or failure to reach the required annual point total, must be reported in the Annual Report.
- c. The permittee is not limited to implementation of the BMPs listed in the above table. Several other BMPs may be implemented, however, only implementation of the BMPs listed in the table may be documented and counted toward the required annual point total.

Kansas Permit No.: M-AR64-SU01 Page 15 of 57

3. Illicit Discharge Detection and Elimination

The permittee shall:

- a. Continue to implement and enforce a program to detect and eliminate illicit discharges into the MS4.
- b. Maintain a storm sewer system map of the permittee's MS4, showing the location of all outfalls, either pipes or open channel drainage, showing the names and location of all streams or lakes receiving discharges from those outfalls. A copy of the map shall be submitted to KDHE with the annual report if requested by KDHE. This map may be submitted as a PDF file(s) on a compact disk (CD) or a digital versatile disk (DVD).
- c. Implement and enforce an ordinance, a resolution, or other enforceable requirement, if the permittee has the authority to do so, to prohibit non-stormwater discharges into the storm sewer system and implement appropriate enforcement procedures and actions. A copy of the ordinance or resolution shall be submitted to KDHE with the annual report if requested by KDHE.
- d. Inform public employees, businesses, and the general public of hazards associated with illegal discharges and improper disposal of waste.
- e. Develop and implement a plan to detect/inspect for and address prohibited non-stormwater discharges, including illegal dumping, to the storm sewer system. The plan must include efforts to identify and evaluate dry weather MS4 discharges to detect and eliminate any associated illicit discharge. Unless identified by either the permittee or KDHE as a significant source of pollutants to waters of the state, several types of non-stormwater flow are not normally prohibited from entering the Municipal Separate Storm Sewer System:

Discharges which are not necessarily prohibited include:

- I. Water line flushing
- II. Diverted stream flows
- III. Rising ground waters
- IV. Uncontaminated groundwater infiltration as defined under 40 CFR 35.2005(20) to separate storm sewers
- V. Uncontaminated pumped groundwater
- VI. Contaminated groundwater if authorized by KDHE and approved by the municipality
- VII. Discharges from potable water sources
- VIII. Foundation drains
 - IX. Air conditioning condensation
 - X. Irrigation waters
 - XI. Springs
 - XII. Water from crawl space pumps

Kansas Permit No.: M-AR64-SU01 Page 16 of 57

- XIII. Footing drains
 - XIV. Lawn watering
 - XV. Individual residential car washing
- XVI. Occasional not-for-profit car wash activities
- XVII. Flows from riparian habitats and wetlands
- XVIII. Dechlorinated swimming pool discharges excluding filter backwash
 - XIX. Street wash water (excluding street sweepings which have been removed from the street)
 - XX. Discharges or flows from firefighting activities
 - XXI. Heat pump discharge waters (residential only)
- XXII. Treated wastewater meeting requirements of an NPDES permit
- XXIII. Sump pump drains
- XXIV. Other discharges determined not to be a significant source of pollutants to waters of the state, a public health hazard or a nuisance.
- f. The implementation of BMPs for this minimum control measure must result in accumulation of a minimum of 5 points total on an annual basis for calendar years 2021 and 2022. The point total requirement increases to 7 points for each calendar year beginning in 2023. The following table lists various BMPs, measurable goals, and the required timing-period or implementation-schedule to qualify for the points in the year.

In cases where the permittee is already implementing a BMP which qualifies for points, they may continue implementation of the BMP and earn the listed points as allowed for the first year of implementation under this permit as well as subsequent years.

Multiple BMPs involve holding public hearings or public forums; a single public hearing or public forums can be held which addresses multiple topics and points claimed for all of the multiple BMPs implemented.

In addition to implementing an Illicit Discharge Detection and Elimination program as required above, the permittee must implement sufficient listed BMPs in the table below to qualify for the required number of points.

BMP Summary	Measurable Goal	Implementation Time Schedule	Points
Lbmp I D D & E - 01			
Hold a public hearing or public forum to educate the public about illicit discharges and alternate acceptable methods of disposal or reuse of substances and/or materials.	Provide public notice of the hearing/forum, invite local news media (either newspaper, radio or TV), and document the hearing with attendance sign-in sheet and minutes of the hearing which include questions/comments from the attendees and answers/comments from the permittee staff.	Retain copies of the notices to public, invitations to attend, attendance sign-in sheets, and minutes. Hearing must be held in year for which points are claimed.	2 points may be claimed for any year a hearing/forum is held.
Lbmp I D D & E - 02			
Implement a program to abandon failed or failing residential or commercial on-site wastewater treatment facilities. These onsite wastewater treatment systems such as septic tank - lateral systems or lagoon systems are then connected to the municipal wastewater collection system for treatment of wastewater at the municipal wastewater treatment plant. Alternately, upgrade or replace the failed system to restore performance.	Redirect the wastewater generated by the facility to the municipal wastewater treatment collection system for proper treatment and disposal. Alternately, upgrade or replace the failed system with improvements which meet or exceed the present code or local requirements.	For each failed or failing on-site system which is abandoned, and the wastewater is redirected to the municipal wastewater treatment system, the permittee may claim points in the year the system is initially connected into the municipal wastewater treatment system. Alternately, for systems which are upgraded or replaced to restore adequate performance a lower number of points may be claimed in the year the upgrade or replacement is completed.	3 points may be claimed for each abandoned system in the year it is abandoned, alternately for systems which are upgraded or replaced as per the requirements a total of 2 points may be claimed in the year upgrade or replacement is completed.
Develop a spill response plan and, if	The plan shall include, at a minimum,	The plan may be implemented in any	3 points may be claimed in the year initially implemented,
appropriate, coordinate emergency	explanation of appropriate spill	year and points claimed for the	and

response with other	response activities	initial	2
agencies or	for spills associated	implementation or	2 points may be claimed
organizations.	with vehicle	for each year the	for each
	accidents, at grade or	plan remains	successive
	above ground storage	effective.	year the plan
	tanks, and vehicle		remains
	fluids from mechanical		effective.
, ,	equipment such as		CITECLIVE.
	construction		
	equipment, cars, or		Personal Property and the second
	trucks. The written		
	plan shall be	A STATE OF THE STA	
Then T.D.D.C.T. O4	maintained on file.		the state of the s
Lbmp I D D & E - 04			1 point may
			be claimed in
Implement a program to	When at least 5% of	The evaluation of a	the year when
evaluate MS4 outfalls	the known MS4 outfalls	group of at least	a total of at
to identify illicit	are inspected and for	5% of the known MS4	least 5% of
discharges. Inspect	which at least one	outfalls may be	the known MS4
at least 5% of the	outfall was identified	completed all in	outfalls are
known MS4 outfalls	as discharging	one year or may	finally
during a calendar year	(entirely or	occur in up to two	inspected,
and evaluate the ones	partially) flow from	consecutive years	and 2
which have dry weather	an illicit discharge,	and a point can be	additional
discharges. Evaluate	the allotted points	claimed. The	points may be
the water quality of	may be claimed in the	larger number of	claimed in
the dry weather	year when the illicit	points may be	which the
discharges to	discharge is	claimed only for	illicit
recognize non-	eliminated. Document	the year in which	discharge(s),
stormwater	the MS4 outfalls	the illicit	associated with this
contributions and	inspected, the	discharge(s),	group of
trace the source of	outfalls with dry	associated with	evaluated
any illicit discharge.	weather discharges and	this group of	outfalls
	the MS4 outfalls	evaluated outfalls	is/are
	associated with illicit discharges.	is/are eliminated.	eliminated.
Lbmp I D D & E - 05			U TO THE WAY
Distribute a letter	mba labbia (au cal		44 3 18 18
(or flier) and/or e-	The letter (or flier)	The distribution of	
mail along with a	and/or e-mail along	these various	D. 11. 14. 14. 14. 14. 14. 14. 14. 14. 14
press release from a	with the press release shall highlight the	documents, letter	
municipal official	requirements for	(or flier) and/or e-mail along with	
with the intent of	proper disposal of	the press release,	and Shipping and
reaching every	wastes and disposal	shall all occur in	- L SIC 13
resident and business	methods. Copies of	the same month.	A STATE OF THE STA
in the MS4 permit	these documents shall	Permittee may claim	2 points
area. The distributed	be retained on file	these points in the	z pornes
documents shall	along with the	year these	
provide information on	distribution/mailing	documents are	
how to avoid illicit	lists to document	distributed.	
discharges to the MS4,	distribution to the		
i.e., proper disposal	target area (minimum		82 TH 200
methods for common	MS4 permit area) to		
substances or	avoid illicit		
materials often	discharges to the MS4.	The second second	
discharged illicitly.	Provide a link to the	The state of the s	
Provide a link to the	municipal website		

municipal website where applicable ordinances and disposal guidance are posted.	where applicable ordinances and disposal guidance are posted.		
Inspect, by televising pipelines or direct visualization of open channel drainage, 2% of the MS4 system within the permit area all conducted within a 12-month period to aid in identifying illicit discharges as well as evaluate the condition of the storm sewer lines/drainage channels-ditches. If in a 12-month period 10% of the MS4 system is inspected a higher point value may be claimed. Ibmp I D D & E - 07	Generate a summary report of the inspection including the number of linear feet televised, number of linear feet televised, number of linear feet visually inspected, condition comments, illicit discharges identified and the results of efforts to eliminate illicit discharges, e.g., discharge line disconnected and redirected to the sanitary sewer or discharge practice terminated.	The inspection process can occur in a single calendar year or may be conducted over a period extending from one year into the succeeding year. Points may be claimed in the year when the televised and/or visual inspection of this portion of the MS4 system (either 2% or 10%) is completed.	3 points may be claimed for inspection of 2% of the MS4 system, alternately if 10% of the MS4 system is inspected 5 points may be claimed.
Implement a Household Hazardous Waste Collection Program (HHWCP) or document others have implemented such a program to provide such service to all property owners or residents located within the permit area.	Document the residents and property owners within the MS4 permit area were able to dispose of such wastes at the HHWCP during a calendar year. Retain this documentation on file.	The property owners or residents located within the permit area must be able to dispose of waste accepted by the HHWCP throughout a calendar year. Points may be claimed for any such year.	3 points may be claimed for any year in which this BMP was implemented in compliance with the requirements.
Implement a program to increase the reliability of sanitary sewer pump stations above the minimum standard design requirements.	A pump station shall be upgraded to include the following: > A dedicated on- site standby generator shall be installed (with automatic transfer switch) for use	In the year all improvements, as listed under measurable goals, are installed and ready for operation the points may be initially claimed and in subsequent years these improvements remain	5 points may be claimed (for each pump station upgraded in compliance with this BMP) in the first year the improvements, as listed under measurable

when main line operational points power fails. may be claimed.

A dialer

> A dialer system, or telemetry system, or connection to a SCADA system shall be installed to provide real time or nearly real time notification of failures at the pump station which can potentially lead to

sanitary sewer overflow.

> The permittee shall purchase and maintain for immediate operation a trailer mounted motor driven sewage pump for use when the pump station fails to operate. The motor driven pump shall be sized to pump at a rate at least equal to the firm pumping capacity of any sanitary sewer pump station the permittee claims points for under this BMP.

> The pump station shall be modified to facilitate the connection of the trailer mounted pump discharge to the force main and convenient

goals, are installed and ready for operation, 4 points may be claimed for (for each pump station upgraded in compliance with this BMP) each successive year the improvements, as listed under measurable goals, remain operational.

Kansas Permit No.: M-AR64-SU01 Page 21 of 57

	installation of the suction line from the trailer mounted pump into the wet well.		
Lbmp I D D & E - 09			
Provide a contribution to area recycle programs or programs (such as household hazardous waste disposal facilities, e-cycle facilities, paper shred facilities, pharmaceutical disposal facilities etc.) designed to properly dispose of types of waste or materials which have previously been discarded to or adjacent to either the MS4, streams, or lakes within or adjacent to the permittee's permit area. The area program must be within 30 miles from this permit area.	The contributions may be made to programs which take tires, automotive fluids, batteries, or other wastes for which there is any documentation such wastes have been discarded as addressed under the BMP summary. The contributions must total a minimum of \$500 in the year (\$100 in the year for alternative lower population municipalities) which points are claimed. The contributions can be monetary or can be in the form of goods and/or services with an agreed specified value. Contributions may be made to area household hazardous waste programs, private recycle/reuse facilities or civic/volunteer organizations assisting in recycle.	The total value of donation (either in-kind work, materials, supplies or cash) in a minimum amount of \$500 must be made in the year points are claimed. Alternatively, for municipalities with less than 500 population the total value of donation in a minimum amount of \$100 must be made in the year points are claimed.	2 points may be claimed each year this BMP goal is achieved.
Lbmp I D D & E - 10	Generate a summary	The inspection	3 points may be claimed for
Inspect, 5% of the MS4 system Stormwater inlets and/or outfalls within the permit area all conducted within a 12-month period to aid in identifying illicit discharges. If in a 12-month period 15% of the MS4 system inlets and/or outfalls are inspected a higher	report of the inspection including the number of inlets and/or outfalls visually inspected, condition comments, illicit discharges identified and the results of efforts to eliminate illicit discharges, e.g., discharge line	process can occur in a single calendar year or may be conducted over a period extending from one year into the succeeding year. Points may be claimed in the year when the televised and/or visual	inspection of 2% of the MS4 system in the year the required percentage of inlets and/or outfalls are finally inspected, alternately if 15% of the

Kansas Permit No.: M-AR64-SU01 Page 22 of 57

claimed in the year the required percentage of inspections are completed.	redirected to the sanitary sewer or discharge practice terminated.	portion of the MS4 system (either 2% or 15%) is completed.	inspected 5 points may be claimed.
---	--	---	------------------------------------

- g. Documentation of compliance with the goal and implementation time schedule must be maintained on file to claim the associated points. Permittee is responsible for implementing adequate BMPs to comply with the Illicit Discharge Detection and Elimination requirements of this permit and be able to claim at least the required number of points in the calendar years as specified above. Extent of compliance, i.e., equal or exceed the required annual point total or failure to reach the required annual point total, must be reported in the Annual Report.
- h. The permittee is not limited to implementation of the BMPs listed in the above table. Several other BMPs may be implemented, however, only implementation of the BMPs listed in the table may be documented and counted toward the required annual point total.

4. Construction Site Stormwater Runoff Control

The permittee shall continue to maintain a program to reduce pollutants in any stormwater runoff to the MS4 from construction activities that result in a land disturbance of greater than or equal to one acre. Reduction of pollutant discharge associated with stormwater from construction activity disturbing less than one acre must be included in the program if that construction activity is part of a larger common plan of development or sale that would disturb one acre or more. The program must include, at a minimum, all the following:

- a. Maintain and enforce an ordinance, a resolution, or other enforceable requirement, if the permittee has the authority to do so, to require erosion and sediment controls, as well as sanctions to ensure compliance, to the extent allowable under State and local law. A copy of the ordinance or resolution shall be submitted to KDHE with the annual report if requested by KDHE.
- b. Maintain requirements for construction site owners or operators to implement appropriate erosion and sediment control best management practices.
- c. Maintain requirements for construction site owners or operators to control waste such as discarded building materials, concrete truck washout, chemicals, litter, and sanitary waste at the construction site that are likely to cause adverse impacts to water quality.
- d. Maintain procedures for site plan review which incorporate consideration of potential water quality impacts.
- e. Maintain procedures for receipt and consideration of information submitted by the public.
- f. Maintain procedures for site inspection and enforcement of control measures.
- g. The implementation of BMPs for this minimum control measure must result in accumulation of a minimum of 4 points total on an annual basis for each calendar year 2021 and 2022. The point total requirement increases to 6 points for each calendar year beginning in 2023. The following table lists various BMPs, measurable goals, and the required timing-period or implementation-schedule to qualify for the points in the year.

In cases where the permittee is already implementing a BMP which qualifies for points, they may continue implementation of the BMP and earn the listed points as allowed for the first year of implementation under this permit as well as subsequent years.

Multiple BMPs involve holding public hearings; a single public hearing can be held which addresses multiple topics and points claimed for all of the multiple BMPs implemented.

In addition to implementing a Construction Site Stormwater Runoff Control program as required above, the permittee must implement sufficient listed BMPs in the table below to qualify for the required number of points.

BMP Summary	Measurable Goal	Implementation Time Schedule etc.	Points
Lbmp C S S R C - 01			3 points may
Implement a requirement for a Soil Erosion and Sediment Control (SESC) Plan for any land Disturbance sites which are either equal to or greater than 1 acre or for which there is construction activity disturbing less than one acre which is part of a larger common plan of development or sale that in total disturbs one acre or more.	Enact a regulatory ordinance, or other enforceable measure that requires an SESC Plan for all developments disturbing sites which are either equal to or greater than 1 acre or for which there is construction activity disturbing less than one acre which is part of a larger common plan of development or sale that in total disturbs one acre or more.	Points may be claimed in the year the ordinance/enforceab le requirement first becomes effective, and for each full calendar year thereafter for which the ordinance/enforceab le requirement remains effective.	be claimed in the year the ordinance initially becomes effective, and 2 points may be claimed for each successive year thereafter for which the ordinance remains effective.
Develop and adopt a design manual for erosion and sediment control BMPs which are required to be used on sites which will be disturbed and are either equal to or greater than 1 acre or for which there is construction activity disturbing less than one acre which is part of a larger common plan of development or sale that in total disturbs one acre or more.	Require implementation of BMPs in compliance with the design manual on all sites which meet the disturbed area standard as specified in the BMP Summary.	Points may be claimed for the year which the manual is initially adopted and implemented, and a reduced number of points may be claimed for subsequent years in which the manual remains implemented.	3 points may be claimed in the year the manual is initially implemented, and 2 points may be claimed for each successive year the manual remains effective.

Lbmp C S S R C - 03			
Provide access to at least one training class for contractors, developers or others involved with land disturbance projects which provides training on requirements for a Stormwater Pollution Prevention Plan (SWP2 Plan) and implementation	This training class must address all local requirements for a SWP2 Plan, requirements for implementation of BMPs and address the requirements for permits.	Points may be claimed for the year in which the training class is held.	3 points
of appropriate BMPs. Lbmp C S S R C - 04			
Develop a site plan review process which considers potential water quality impacts which may occur during construction as well as post construction impacts.	Review process must have written guidance for the reviewer. Issuance of a building permit or approval to start construction may not be provided until the site plan has successfully passed the review process either based on the initial site plan submittal or has been modified to comply with requirements identified during the review process. Measures must be included to enforce the installation of water quality BMPs included in the site plan.	Points may be claimed in the year the review process is initially developed and implemented. Also points may be claimed in each subsequent year the review process continues to be implemented.	3 points may be claimed in the year the review process is initially developed and implemented, 2 points may be claimed for each successive year the review process continues to be implemented.
Establish effective requirements for construction sites to control wastes. Develop through ordinance or other enforceable means requirements for construction site Operators or owners to control wastes. At a minimum control shall be imposed to prevent entry into the MS4 for the following wastes:	Enact ordinance or other effective means to achieve control of wastes at construction sites.	Points may be claimed in the year of enactment. Also points may be claimed in each subsequent year the method of effective control of construction site waste remains in effect.	3 points may be claimed in the year of enactment, 2 points may be claimed for each successive year the method of effective control of construction site waste remains in effect.

Kansas Permit No.: M-AR64-SU01 Page 25 of 57

> discarded building			_
materials > concrete > Truck washout > chemicals, > litter, and			
> sanitary waste			
Lbmp C S S R C - 06			
Develop written procedures for inspection of construction sites. Develop a Stormwater Construction Site Inspection Guide for use by municipal inspectors.	The procedures document must address the administrative aspects associated with required inspections of construction sites, the issuance of inspection reports, notices of violations, and enforcement actions. The Inspection Guide must provide inspectors guidance on how to conduct a construction site stormwater inspection, the required procedures, and guidance on acceptable conditions of various BMPs employed on such sites, enforcement actions and/or reference of cases for enforcement by other municipal staff, guidance on photo log of the inspection and inspection checklists for use by the inspector.	Development of the written procedures and the Inspection Guide can occur in any year. Initial implementation can allow points to be claimed in that year and continued implementation can allow points to be claimed in subsequent years.	3 points may be claimed in the year of initial development, 2 points may be claimed for each successive year the written procedures and inspection guide continue to be utilized.
Lbmp C S S R C - 07			1 point may be claimed for any year
Acquire or develop a software tracking system to track inspections and related tasks.	The tracking system must allow for scheduling inspections and follow-up activities such as reinspections, mailing notices or reports, etc.	A point can be claimed in the initial year the software tracking system is implemented and each year thereafter it is utilized.	the software is initially utilized, and 1 point may be claimed for each successive year the software is utilized.

- h. Documentation of compliance with the goal and implementation time schedule must be maintained on file to claim the associated points. Permittee is responsible for implementing adequate BMPs to comply with the Construction Site Stormwater Runoff Control requirements of this permit and be able to claim at least the required number of points in the calendar years as specified above. Extent of compliance, i.e., equal or exceed the required annual point total or failure to reach the required annual point total, must be reported in the Annual Report.
 - i. The permittee is not limited to implementation of the BMPs listed in the above table. Several other BMPs may be implemented, however, only implementation of the BMPs listed in the table may be documented and counted toward the required annual point total.

5. Post-Construction Stormwater Management in New Development and Redevelopment Projects

The permittee shall continue to maintain a program to address post-construction stormwater runoff from new development and redevelopment projects that disturb greater than or equal to one acre, including projects less than one acre that are part of a larger common plan of development or sale, that discharge into the MS4. The program must include, at a minimum, all the following:

- a. Maintain a requirement for BMPs to prevent or minimize adverse water quality impacts.
- b. Maintain strategies which include a combination of structural and/or non-structural BMPs appropriate for the municipality.
- c. Maintain and enforce an ordinance or resolution, if the permittee has the authority to do so, to address post-construction runoff from new development and redevelopment projects to the extent allowable under State and local law.
- d. Ensure adequate long-term operation and maintenance of structural BMPs.
- e. The implementation of BMPs for this minimum control measure must result in accumulation of a minimum of 5 points total on an annual basis for each calendar year 2021 and 2022. The point total requirement increases to 7 points for each calendar year beginning in 2023. The following table lists various BMPs, measurable goals, and the required timing-period or implementation-schedule to qualify for the points in the year.

In cases where the permittee is already implementing a BMP which qualifies for points, they may continue implementation of the BMP and earn the listed points as allowed for the first year of implementation under this permit as well as subsequent years.

Multiple BMPs involve holding public hearings; a single public hearing can be held which addresses multiple topics and points claimed for all of the multiple BMPs implemented.

In addition to implementing a Post-Construction Stormwater Management in New Development and Redevelopment Projects program as required above, the permittee must implement sufficient listed BMPs in the table below to qualify for the required number of points.

BMP Summary	Measurable Goal	Implementation Time Schedule etc.	Points
Lbmp P-C S M - 01			
	The custom design manual shall impose requirements to achieve at least one of the following standards: Capture, at least, the first 0.5 inches of precipitation on the development/re- development site and utilize methods to prevent discharge off- site, including but not limited to: retain on- site infiltrate evaporate transpire or beneficial ly reuse Through implementation of appropriate BMP(s) reduce the peak stormwater flow rate to a value equal to or less than the rate which would be	, -	Points 4 points may be claimed in the year of initial implementation of a custom design manual - alternately 6 points may be claimed in the year of initial implementation of the APWA 5600 stormwater design criteria and the MARC/APWA BMP Manual, 3 points may be claimed for each successive year compliance with the custom design manual is required/imple -mented Alternately 5 points may be claimed in each successive year the implementation of the APWA
	experienced on the site prior to the development/re-		5600 stormwater design
	development project based upon modeling a		criteria and the MARC/APWA BMP Manual is
0	standard storm event, e.g. 1.0 inch - 6-hour		required/imple -mented.
	event assuming saturated soil		
	conditions.		

with the design of projects prior to site plan review by the permittee. Lbmp P-C S M - 03 Develop and implement a program to ensure adequate	The program shall be detailed in a written document and made	Development of the program can occur in any year.	3 points may be claimed in the year of initial implementation
Develop a list of post-construction structural or non-structural BMPs which are required to be incorporated in any development/re-development project. The list must include guidance regarding the BMPs which must be incorporated in various projects as determined appropriate by the permittee. The list is to be provided to entities involved	Development and implementation of the list and guidance is necessary to claim points in the first year. The list of required BMPs must be enforceable through ordinance or other means.	Development of the list and guidance can occur in any year. Initial implementation can allow points to be claimed in that year and continued implementation can allow points to be claimed in subsequent years.	3 points may be claimed in the year of initial implementation , 2 points may be claimed for each successive year the list is maintained and
	Measures must be included to enforce the installation of the various structural BMPs required.		
	As an alternative to a custom design manual the APWA 5600 Stormwater Design Criteria and the MARC/APWA BMP Manual may be adopted and implemented.		
	> Other sizing or detention standards generally accepted by design engineers as adequate for the permittee's local.		

long-term cleaning, available to all Initial 2 points may operation and pertinent maintenance implementation can be claimed for maintenance of all staff. allow points to be each municipally owned or claimed in that successive operated postvear and continued year the construction implementation can program is structural stormwater allow points to be maintained and BMP facilities. The claimed in utilized. program shall address subsequent years. several different types of these BMP systems. The systems, which are addressed, shall include any type of post-construction structural BMP system, contained in the MS4. These shall include, if so present, at a minimum the following: > detention ponds > retention ponds > grass swales > pervious paving systems wetlands > vegetative filter strips manufactured stormwater treatment devices (swirl separators, screens, etc.) > drop inlet-catch basin Lbmp P-C S M - 04 Develop a master plan Runoff problems can be After all aspects or comprehensive addressed efficiently are implemented 5 points may development plan which with sound planning including final be claimed in establishes zoning and procedures. This implementation of the year all development standards master or the master or aspects are with establishment of comprehensive comprehensive initially both structural and development plan must development plan, implemented, non-structural BMPs include, if not along with 2 points may intended to avoid or already implemented, a enactment of the be claimed for minimize adverse water zoning ordinance, a required each quality impacts poststream buffer ordinances points successive construction. ordinance, site plan for implementation year all development of this BMP can aspects requirements which initially be continue to be include minimizing the claimed. implemented. increase of impervious surfaces and maximization/preservat

ion of open space.

	The plan must also impose requirements for new development or re-development projects to utilize stormwater retention or detention BMPs and vegetative BMPs (such as grassy swales, filter strips, artificial wetlands, and rain gardens).		
Develop and implement a program for inspection of permittee owned	The program shall require inspection of at least 10% of the structural BMPs on an annual basis	The program shall be developed and implemented within a single year.	
structural BMPs which includes implementation of needed maintenance to ensure long-term operation of the BMPs	Identified maintenance activities shall be completed: 1. in the same year of inspection or 2. completed as dictated by the permittee's maintenance/O&M plan 3. or a written plan for completion of the necessary maintenance shall be completed in the same year of inspection with the objective for completion		3 points may be claimed in the year the program is initially developed and implemented, 2 points may be claimed for each successive year the program continues to be implemented.
	of the maintenance activity within 18 months.		Garage William
Lbmp P-C S M - 06 Develop and implement a program for inspection of known privately owned structural BMPs which includes providing the	The program shall require inspection of at least 10% of the known privately owned structural BMPs on an annual basis.	The program shall be developed and implemented within a single year.	3 points may be claimed in the year the program is initially developed and implemented, 2 points may be claimed for

owner of the BMPs an inspection report which specifies needed maintenance to ensure long-term operation of the BMPs.	Identified maintenance activities shall be completed in the same year of inspection or a written plan for completion of the necessary maintenance shall be completed in the same year of inspection with the objective for completion of the		each successive year the program continues to be implemented.
Lbmp P-C S M - 07	maintenance activity within 18 months.		3 points may
Enact either an ordinance, a resolution, or other enforceable requirement which requires the installation of pervious surfaces on property.	The ordinance or resolution or other enforceable requirement must specify when installation of impervious surfaces is not acceptable and what allowable pervious surfaces can be installed in lieu of impervious surfaces.	The year the ordinance or resolution or other enforceable requirement is implemented points may be claimed and continued implementation can allow points to be claimed in subsequent years.	be claimed in the year of initial implementation 2 points may be claimed for each successive year the ordinance or resolution or other enforceable requirement is implemented.
Implement a program to encourage residential owners to install stormwater BMPs, including but not limited to, native trees, native flower gardens, rain gardens, rain barrels, pervious surfaces, and vegetated swales.	A program which results in installation of such BMPs on 1% of the residential parcels in a year will allow two points to be claimed for that year. In a year when installation of such BMPs on 5% of the residential parcels occurs, a larger number of points may be claimed.	The number of residential parcels improved to qualify for points must occur in a single calendar year.	2 points may be claimed in a year BMPs are installed on 1% of the residential parcels, 4 points may be claimed in a year BMPs are installed on 5% of the residential parcels.

- f. Documentation of compliance with the goal and implementation time schedule must be maintained on file to claim the associated points. Permittee is responsible for implementing adequate BMPs to comply with the Post-Construction Stormwater management in New Development and Redevelopment Projects requirements of this permit and be able to claim at least the required number of points in the calendar years as specified above. Extent of compliance, i.e., equal or exceed the required annual point total or failure to reach the required annual point total, must be reported in the Annual Report.
- g. The permittee is not limited to implementation of the BMPs listed in the above table. Several other BMPs may be implemented, however, only implementation of the BMPs listed in the table may be documented and counted toward the required annual point total.

6. Pollution Prevention/Good Housekeeping for Municipal Operations

The permittee shall continue to implement an operation and maintenance program that includes employee training to prevent and reduce stormwater pollution from municipal operations activities such as park and open space maintenance, fleet and building maintenance, new construction and land disturbances, and stormwater system maintenance.

a. The implementation of BMPs for this minimum control measure must result in accumulation of a minimum of 4 points total on an annual basis for each calendar year 2021 and 2022. The point total requirement increases to 6 points for each calendar year beginning in 2023. The following table lists various BMPs, measurable goals, and the required timing-period or implementation-schedule to qualify for the points in the year.

In cases where the permittee is already implementing a BMP which qualifies for points, they may continue implementation of the BMP and earn the listed points as allowed for the first year of implementation under this permit as well as subsequent years.

Multiple BMPs involve holding public hearings; a single public hearing can be held which addresses multiple topics and points claimed for all of the multiple BMPs implemented.

In addition to implementing a Pollution Prevention/Good Housekeeping for Municipal Operations program as required above, the permittee must implement sufficient listed BMPs in the table below to qualify for the required number of points.

BMP Summary	Measurable Goal	Implementation Time Schedule etc.	Points
Install a screening device or method at a single municipal storm sewer outfall or on the storm sewer line immediately upstream of the outfall to reduce the discharge of floatables or other	The screening device or method is required to remove objects that exceed at least 1½ inches in size. The device or method must be capable of continuous operation	Volume or weight of the material shall be documented for either each discharge event or on a quarterly basis.	3 points may be claimed in the year the screening device or method is initially implemented, 2 points may be claimed for each successive

objects to receiving waters.	during stormwater discharges. An emergency bypass or overflow line can be included to avoid surcharging/flooding in the event the screening device or method fails to operate properly at any time. A log of the material captured and prevented from discharge to the receiving water shall be maintained.		year the screening device or method continues to be implemented.
Implement a recycle and proper waste disposal program for municipal staff to reduce potential for litter, to recycle waste oil, batteries, glass containers, plastic containers, and paper products.	A log of the materials directed to recycle shall be maintained. Entries in the log shall record either weight or volume of recycle materials removed from the containers and transported to the recycle facility as well as the date of transport.	Recycle containers shall be available for staff use all days of the year in which points are claimed.	3 points may be claimed in the year recycle containers are made available for municipal staff use and the recycle program is initially implemented, 2 points may be claimed for each successive year the recycle program continues to be implemented.
Develop a guidance document for municipal staff or third-party contractors which apply pesticides. The guidance shall require any municipal staff, who apply restricted use pesticides, to have a commercial applicator certification from the Kansas Department of Agriculture if	Require staff which apply pesticides to use such pesticides in compliance with the guidance document. The guidance document must require use of pesticides in compliance with the label instructions.	The guidance document must be finalized and implemented in the year which points are initially claimed.	2 points may be claimed in the year the guidance document is finalized and implemented, 1 point may be claimed for each successive year the guidance document continues to be implemented.

required by that			
required by that Department.			
Lbmp P P/G H - 04			
Implement a program, with guidance to municipal staff or third-party contractors, to ensure any municipal vehicle or other mechanical equipment washing is conducted in a manner which ensures the wash water is disposed of in the sanitary sewer or otherwise receives proper treatment prior to discharge to the environment.	Maintain proper wash facilities for municipal staff to wash vehicles and/or equipment or implement a program which includes guidance to municipal staff to take vehicles and/or equipment to commercial wash facilities, either of which ensures the wash water is conveyed to the sanitary sewer, or otherwise receives proper treatment prior to discharge to the environment, and not discharged untreated to the MS4 or directly to the environment.	The guidance document must be finalized and implemented in the year which points are initially claimed.	2 points may be claimed in the year the guidance document is finalized and implemented, 1 point may be claimed for each successive year the guidance document continues to be implemented.
Implement a program for street sweeping in which the street sweepings are collected and disposed of properly or recycled/reused if possible.	All paved streets which can be swept shall be listed in the schedule for street sweeping. A log shall be maintained listing the street segments which are swept and, dates of sweeping and where the street sweepings are disposed or where the material was sent to be recycled and/or reused. Alternatively, for municipalities with less than 500 population street sweeping can be limited to sweeping the gutters. The log which must be maintained need only indicate the street	At least 10% of the streets which are listed in the street sweeping schedule must be swept at least once in a year to claim points for the year. In years when street sweeping equipment is purchased for use by the permittee additional points may be claimed. Alternately, for municipalities with less than 500 population at least 5% of the street gutters which can be swept must be swept in a year to claim points for the year.	3 points may be claimed in the year at least 10% of the listed streets are swept and street sweeping equipment is purchased, 2 points may be claimed for each year at least 10% of the listed streets are swept or alternately for municipalities with less than 500 population if at least 5% of the street gutters which can be swept are swept in a

	swept in the year and confirm the sweepings were properly disposed or recycled and/or reused		may be claimed.
Develop an employee training program to ensure permittee's staff understand what actions they can take in the workplace to minimize stormwater pollution.	-	For each year in which staff receive guidance documents or in-person training or video training on two separate dates, points may be claimed for the year.	In years when guidance documents or training (inperson or video) are provided on two separate dates 1 point may be claimed.
	minimum of twice per year.		
Lbmp P P/G H - 07			In years when staff inspect at least 5% of
Implement a program to inspect stormwater inlets to identify illicit discharges and clean drop inlets of accumulated debris.	Inspect at least 5% of all inlets annually. Additionally, if 10% of all inlets are inspected in a year an additional point may be claimed. For any inlets which have evidence of dumped paint, oil or other substances which are considered illicit discharges follow up with efforts to educate individuals near the impacted	For each year in which staff inspect at least 5% of all stormwater inlets at least one point may be claimed.	at least 5% of all stormwater inlets and remove accumulated debris 1 point may be claimed. In years when staff inspect at least 10% of all stormwater inlets and remove accumulated debris 2 points may be claimed.

	inlot shout illiant		
	inlet about illicit discharges.		
	For inlets which have any accumulation of debris, remove the debris for proper disposal.		
Lbmp P P/G H - 08			
Develop, implement and keep updated an online storm sewer map accessible to the public.	Map shall cover the entire MS4 within the permit area and include all the MS4 lines both pipe and open drainage (i.e. ditches) and shall also illustrate all impaired waterways (i.e. 303(d) listed and TMDL listed streams/rivers) with an indication of the listed impairment.	For each year in which the map is posted online points may be claimed. In the first year the map is posted it must be posted for at least six months for points to be claimed.	3 points may be claimed in the first year, 2 points may be claimed for each year thereafter for which the map remains posted.
Identify permittee owned facilities, open space and buildings that can be retrofitted for stormwater BMPs.	Retrofit projects can include: green infrastructure, catchment improvements, Pollutant of Concern targeted BMPs, and native plant restoration projects.	The site(s) must be retrofitted with stormwater BMPs as listed in the measurable goals. Points can be awarded in the first year the BMPs are installed and begin operation and points may be claimed for each year the retrofitted BMPs continue to be operated.	l point may be claimed in the first year for each site retrofitted (up to two sites/points maximum, 2 points may be claimed for each year at least two sites continue to operate all of the retrofitted BMPs which were installed.
Install and operate a constructed wetland at a municipal facility such as at a parking lot, shop, maintenance facility, rest area or any other industrial/commercial type facility, e.g. recycling facility,	The wetland shall include a water surface area of at least 1/4 acre or equivalent submerged surface area for submerged wetlands.	Points may be claimed in the year the wetland is constructed and in subsequent years the wetland remains in operation.	2 points may be claimed for the year in which the wetland is constructed, 1 point may be claimed for each subsequent year the wetland

transfer station, kennel, or airport.			remains in operation.
Lbmp P P/G H - 11			
Install a canopy or other covered area for load-out of salt or other de-icing chemicals where such de-icing materials are stored either within the permit area or a storage facility located within 30 miles of this permit area. The canopy or other covered area for load-out of salt or other de-icing materials may be installed at a facility owned by the permittee or at a facility owned by an entity the permittee contracts with as long as the facility is located within 30 miles of this permit area.	The canopy or covered area shall be large enough to allow normal load-out and cleanup of spilled de-icing materials, without mixing with precipitation and resulting in contaminated runoff from the site, during and immediately following load out operations	Points may be claimed in the initial year of construction and in subsequent years the canopy/covered area remains in operation.	3 points may be claimed for the year in which the canopy/covered area is constructed, 2 points may be claimed for each subsequent year the canopy/covered area remains in operation.
Install a stormwater treatment system for capture of either trash, sediment, or debris. Systems may include any proprietary stormwater treatment system including CDS, Hancor, Enviro 21, etc. or similar custom designed systems. A system can be installed at a single municipal storm sewer outfall or on the storm sewer line immediately upstream of the outfall to reduce the discharge of floatables or other objects to receiving waters. Alternately,	The treatment system or method must be capable of continuous operation during stormwater discharges. An emergency bypass or overflow line can be included to avoid surcharging/flooding in the event the system is overloaded or fails to operate properly at any time. A log of the material (noting either volume or weight) captured and prevented from discharge to the receiving water shall be maintained.	Volume or weight of the material shall be documented for either each discharge event, on a quarterly basis or at least annually.	3 points may be claimed in the year the treatment system is initially implemented, 2 points may be claimed for each successive year the treatment system continues to be implemented.

Kansas Permit No.: M-AR64-SU01 Page 38 of 57

stormwater line to	
0001111100001 11110000	
provide treatment at	
problem locations.	

- b. Documentation of compliance with the goal and implementation time schedule must be maintained on file to claim the associated points. Permittee is responsible for implementing adequate BMPs to comply with the Pollution Prevention/Good Housekeeping for Municipal Operations requirements of this permit and be able to claim at least the required number of points in the calendar years as specified above. Extent of compliance, i.e., equal or exceed the required annual point total or failure to reach the required annual point total, must be reported in the Annual Report.
- c. The permittee is not limited to implementation of the BMPs listed in the above table. Several other BMPs may be implemented, however, only implementation of the BMPs listed in the table may be documented and counted toward the required annual point total.

Guidance useful in implementing the six minimum control measures can be obtained from the Online Water Library (OWL) of the Center for Watershed Protection. A list of url links to helpful guidance documents, including OWL, can be found on the KDHE Municipal Stormwater Program website at the following url:

http://www.kdheks.gov/muni/download/MS4 NPDES Permit helpful quidance.pdf

Document titled "MS4 NPDES Permit Helpful Guidance and/or Resources"

D. Total Maximum Daily Load (TMDL) Regulated Pollutants

The Permittee shall continue to review, update, implement and develop, when necessary, structural and non-structural BMPs which will reduce to the Maximum Extent Practicable the discharge of the TMDL regulated pollutants from the MS4 as listed in PART II.

The effort to reduce the discharge of TMDL regulated pollutants is anticipated to be an iterative process with changes in the SMP periodically, generally not more frequently than annually, possibly every two or three years. This "adaptive management" type process is recommended to attenuate the discharge of TMDL regulated pollutants listed in the TMDL Table of PART II of this permit.

Kansas Permit No.: M-AR64-SU01 Page 39 of 57

Each updated SMP document shall provide:

1. Best Management Practices (BMPs)

Updates of the SMP document can include structural and/or non-structural BMPs implemented to reduce the discharge of TMDL regulated pollutants from the MS4. This section of the SMP shall identify or include:

a. BMPs which will be implemented, including non-structural and/or structural measures, as selected from EPA's "National Menu of Best Management Practices (BMPs) for Stormwater" or from a local or regionally appropriate storm drainage criteria manual such as the Kansas City Metro Chapter of the American Public Works Association (APWA) Manual of Best Management Practices for Stormwater Quality or such other BMP manuals as are appropriate (links for the National Menu of Best Management Practices (BMPs) for Stormwater and the Kansas City Metro Chapter of the American Public Works Association (APWA) Manual of Best Management Practices for Stormwater Quality can be found on the KDHE document titled "MS4 NPDES Permit Helpful Guidance and/or Resources" at the following url:

http://www.kdheks.gov/muni/download/MS4 NPDES Permit helpful guidance.pdf

- b. Include a description of non-structural practices being implemented, including the six minimum control measures and/or other source control measures.
- c. Include the location of the structural BMPs.
- d. Identify the design factors associated with the structural BMPs.
- e. Include information on the reported effectiveness of the chosen BMPs based on regionally appropriate data or performance analyses in the International Stormwater BMP Database (a link to the Database can be found on the KDHE document titled "MS4 NPDES Permit Helpful Guidance and/or Resources" at the following url:

http://www.kdheks.gov/muni/download/MS4 NPDES Permit helpful guidance.pdf

- f. Include a schedule for constructing and/or implementing additional selected BMPs to reduce the discharge of TMDL regulated pollutants.
- g. Include an inspection/maintenance plan and schedule for each BMP, as appropriate.
- h. Include a plan and schedule to monitor the effectiveness of the BMPs to reduce the discharge of TMDL regulated pollutants

2. Measurable goals to assess the effectiveness of the TMDL BMPs

Overall TMDL measurable goals should be based upon in stream sampling of the stream(s) existing in, or adjacent to the Permit Area (or Permit Areas for cooperative stormwater control efforts as provided in paragraph 4 below) during or immediately following storm events. Alternately, the TMDL measurable goals may be based on stormwater sampling within the MS4 comparing results upstream of the BMP and downstream of the BMP. The monitoring results of samples obtained to determine performance of BMPs should be maintained on file in compliance with the Standard

Conditions records retention requirement, these results do not need to be reported to KDHE via the electronic DMR process at this time. However, these monitoring results are to be reported or summarized in the Annual Report as required in PART V $\underline{\text{REPORTING}}$.

Individual or sub-basin BMP performance goals may include in stream or BMP discharge sampling locations based upon individual BMPs, sub-basin BMPs or aggregate BMPs. Alternatively, the permittee may use modeling that has been properly calibrated to determine that BMP measurable goals are being met.

Measurable goals for reducing TMDL pollutants contributed by MS4s can be expressed in quantifiable values to:

- I. reduce the total mass of pollutants, and
- II. be expressed as average and median values (percent reduction of inflow volume, reduction in pollutant mass loading) or for bacteria as a geometric mean.

3. Maps shall be developed and maintained which illustrate:

- I. The Permit Area, boundaries of the contributing drainage basins and primary sub-basins, within and outside the Permit Area
- II. The locations of the BMPs, if structural
- III. The location of TMDL stream monitoring locations, if such monitoring is required
 - IV. Storm sewer collection system which includes the outfalls within the Permit Area where the MS4 drains to TMDL listed impaired streams or lakes

4. Alternative Stormwater Offsite Pollution Reduction Program

As appropriate, when waters of the state are affected by TMDL regulated pollutants from both the Permit Area and surrounding non-jurisdictional lands, the permittees may incorporate and implement plans through their SMP for an offsite pollution reduction program to install Best Management Practices (BMPs) in alternative locations, including outside the Permit Area, within the watershed shared by urban entities or urban and non-urban entities. Any alternative stormwater offsite pollution reduction program should be developed with watershed interests, such as other communities, Watershed Restoration and Protection Strategy (WRAPS) groups and Conservation Districts lying outside the Permit Area for the joint purpose of reducing pollutant loads generated from urban and non-urban lands within the shared watershed. Candidate offsite locations and practices will be consistent with implementing existing watershed plans that identify specific urban and non-urban (such as agricultural) BMP types and locations to achieve TMDLs reductions. The Alternative Stormwater Offsite Pollution Reduction Program shall be subject to KDHE approval and approved by KDHE prior to incorporation into the permittee's SMP.

- E. The parties responsible for compliance with the SMP document.
- F. Monitoring Requirements

Possibly required in PART II.

Kansas Permit No.: M-AR64-SU01 Page 41 of 57

G. Reporting Requirements

See PART V.

H. Modifications to BMPs and the Stormwater Management Program document

For minor BMP modifications/replacement: Within 60 days of a determination by the permittee or date of written notification from KDHE, the permittee shall modify the BMP if modifications are needed to maintain a program in compliance with this permit.

For major BMP modifications/replacement: These major modifications are defined as ones which normally take more than 60 days to construct and/or implement. Within 60 days of a determination by the permittee or date of notification from KDHE, the permittee shall provide a plan and schedule for the upgrade/replacement of the BMP. The plan and schedule are subject to KDHE approval.

The SMP shall be evaluated annually and, if revisions are necessary, the modified SMP document shall be submitted with the annual report due to KDHE by February 28 of each year.

PART II. TOTAL MAXIMUM DAILY LOAD (TMDL) BEST MANAGEMENT PRACTICES AND SURFACE WATER MONITORING

Permittees who are required to complete storm event monitoring of surface waters, i.e., streams or rivers, (see TMDL Table and associated text) shall report the results of the storm event monitoring with the eDMR reporting system.

A. TMDL BMP IMPLEMENTATION REQUIREMENTS

The implementation of BMPs for this minimum control measure must result in accumulation of a minimum of 4 points total on an annual basis for each calendar year 2021 and 2022. The point total requirement increases to 6 points for each calendar year beginning in 2023. The following table lists various BMPs, measurable goals, and the required timing-period or implementation-schedule to qualify for the points in the year.

In cases where the permittee is already implementing a BMP which qualifies for points, they may continue implementation of the BMP and earn the listed points as allowed for the first year of implementation under this permit as well as subsequent years.

Multiple BMPs involve holding public hearings; a single public hearing can be held which addresses multiple topics and points claimed for all of the multiple BMPs implemented.

In addition to implementing a TMDL Pollutant Reduction and Monitoring program as required above, the permittee must implement sufficient listed BMPs in the table below to qualify for the required number of points.

BMP Summary	Measurable Goal	Implementation Time Schedule etc.	Points
Install pet waste stations which include a glove/bag dispenser with signage and waste can to encourage pet waste disposal at either parks, trails,	At least one pet waste station shall be installed at the selected park, trail, rest area or other public land. The station(s) shall	In the year the Measurable Goal requirement is implemented the point may be claimed and for each year	1 point may be claimed for the year in which the Measurable Goal requirements are enacted, and

rest areas or other public lands owned by the permittee.	include signage which encourages proper pet waste disposal/cleanup and a waste can.	thereafter the pet waste stations remain in use.	l points may be claimed for each subsequent year the Measurable Goal
			requirements remain in effect.
Establish a program to encourage installation of residential rain gardens.	Provide public education on rain gardens and design guidance for the installation of residential rain gardens. The rain gardens must have a minimum area of 20 square feet. The installation of rain gardens on five various residential parcels shall qualify the permittee to claim points for this BMP.	In the year five or more residential rain gardens are finally constructed and become operational the points may be initially claimed and in subsequent years when at least five residential rain gardens remain operational points may be claimed.	3 points may be claimed for the year in which five or more residential parcels install rain gardens and initiate operation, 2 points may be claimed for each subsequent year at least five or more residential parcels have rain gardens remain in operation.
Install and operate a constructed wetland.	The wetland shall include a water surface area of at least one acre or equivalent submerged surface area for submerged wetlands.	Points may be claimed in the year the wetland is constructed and in subsequent years the wetland remains in operation.	3 points may be claimed for the year in which the wetland is constructed, 2 points may be claimed for each subsequent year the wetland remains in operation.
Lbmp T M D L - 04 Enact a stream buffer ordinance, resolution, or other enforceable requirement to impose stream buffer standards.	The enactment of stream buffer standards must include enforcement capability. Consider use of the EPA stream buffer model ordinance or similar such requirement.	The year the ordinance, resolution or other enforceable requirement is enacted points may be claimed. Also points may be claimed for	3 points may be claimed for the year in which the ordinance, resolution or other enforceable requirement is enacted, 2 points may be claimed for

		subsequent years the ordinance, resolution or other enforceable requirement remains in effect.	each subsequent year it remains in effect.
Lbmp T M D L - 05			
Develop a pet waste brochure or flyer document to educate the public about animal waste contamination of stormwater. The document encourages pet owners to pick up their pet's waste. Alternately, post the document on social media or the municipal website.	The brochures or flyers are to be posted in various public buildings and distributed to the public throughout the year. In the year the number of documents shall equal or exceed the most recent U.S. Census Bureau decennial housing units value for the permit area. The applicable U.S. Census housing units value shall be documented, and the number of documents distributed shall also be documented. This information and copies of the documents shall be retained on file.	The documents may be distributed in any fashion and at any time throughout the year. Documents posted on website(s) shall be posted for at least six months in the year. Documents posted on social media shall be posted six times within the year points are claimed.	1 point may be claimed in a year in which the required number of brochures and/or flyers are distributed, documents posted on social media or the website must be posted for at least as specified.
	social media or the website shall have the page copied and printed to retain on file.		aTir s
Lbmp T M D L - 06			2 points may be claimed in
Distribute "Only Rain Down the Drain" door hangers or similar document.	Provide in portions of the permit area with suspected illicit discharges. In the year the number of documents distributed shall equal or exceed 10% of the most recent U.S. Census Bureau decennial housing units value for the permit area. The applicable U.S. Census housing units value shall be documented, and the number of	The documents may be distributed in any fashion and at any time throughout the year. Alternately, the document may be posted to social media (at least three times in the year) or posted on the municipal website for a minimum of three months in the year	a year in which the required number of hangers or similar documents are distributed or alternately posted to social media or the municipal website for the required time.

	documents distributed shall also be documented. This information and copies of the documents shall be retained on file.	to qualify for points	
Inspect 10% of all known MS4 outfalls for dry weather discharges either annually or twice per year to identify potential illicit discharges. Lbmp T M D L - 08	Complete inspection of all known MS4 outfalls either annually or twice per year during dry weather periods. If dry weather discharge is found follow-up with investigation to determine if a portion or all the discharge is illicit. Document the findings and initiate efforts to eliminate any identified illicit discharges.	The inspections must be conducted either annually or if twice per year they must be seasonal within the same calendar year (winter, spring, summer, and fall). Points can be claimed for that year. In addition, if an illicit discharge is detected and eliminated in association with this inspection program additional points may be claimed in the year detected or in the year the discharge is eliminated.	3 points may be claimed for annual inspection as required by this BMP, 5 points may be claimed for these inspections completed twice in a year, and if an illicit discharge is detected and eliminated. The 2 additional points may be claimed, only once, either in the year detected or in the year the illicit discharge is eliminated.
Implement an Alternative Stormwater Offsite Pollution Reduction Program.	This program will include installation of BMPs in alternative locations, including outside the Permit Area, within the watershed shared by urban entities or urban and non-urban entities. The alternative stormwater offsite pollution reduction program shall be developed with watershed interests, such as other communities, Watershed Restoration and Protection	In the year the Alternative Stormwater Offsite Pollution Reduction Program is approved by KDHE points may be claimed. In subsequent years in which the program is maintained points may be claimed.	5 points may be claimed in the year KDHE approves the program, 4 points may be claimed for each subsequent year it remains in effect.

Kansas Permit No.: M-AR64-SU01 Page 45 of 57

	Strategy (WRAPS)		
	groups and		
	Conservation Districts		
	lying outside the		
	Permit Area for the		
	joint purpose of		
	reducing pollutant		
	loads generated from		
	urban and non-urban		
	lands within the		
	shared watershed.		
	Candidate offsite		
	locations and		
	practices will be		
	consistent with		
,	implementing existing		
	watershed plans that		
	identify specific		
	urban and non-urban		
	(such as agricultural)		
	BMP types and		
	locations to achieve		
	TMDLs reductions. The		
	Alternative Stormwater		
	Offsite Pollution		
	Reduction Program		
	shall be subject to		
	KDHE approval and		
	approved by KDHE prior		
	to incorporation into		
	the permittee's SMP.		
Lbmp T M D L - 09	H -		
Implement a program to	The four litter	The four collection	
collect and properly	collection efforts	efforts must occur	2 points may
dispose of litter, on	should, but are not	in a calendar year.	be claimed for
four separate	required to, occur		
occasions per calendar	seasonally, i.e.,		any year i n which four
year, within areas	winter, spring, summer	0	
where littering has	and fall. If it is		collection
been identified as a	unreasonable to		efforts have
problem. Such areas	collect litter in any		occurred in
may include municipal	season the required		compliance
parks, trails, rest	four collection		with the
areas, or other public	efforts may occur in		requirements
lands owned by the	either three seasons		of this BMP.
permittee.	or in a minimum of two		
The state of the s	seasons.		
	A CONTRACTOR		
Lbmp T M D L - 10			3 points may
			be claimed for
Establish a program to	Provide public	In the year five or	any year in
encourage Rainwater	education on rainwater	more residential	which sufficient
Harvesting.	harvesting and design	rain barrel systems	l .
The top carry.	guidance for the	_	rain
	installation of rain	or one commercial cistern are finally	harvesting
	barrels, cisterns,	constructed and	systems are
L	Tagrecia Craceria,	L constructed and	constructed or

raingardens and other rainwater harvesting devices. When rain barrels are utilized they must be a minimum size of 50 gallons. When raingardens are utilized they must be a minimum of 20 square feet. A rain harvesting system on a commercial setting must have adequate capacity to hold the runoff from the impervious surface for which it is designed to collect on the commercial parcel equal to that generated by a 0.1inch rainfall event. The installation of rain barrels or rain gardens on five residential lots, or the installation of one rain harvesting system in a commercial setting shall qualify the permittee to claim points for this BMP.

become operational the points may be initially claimed and in subsequent years when at least five residential rain barrel systems or one commercial cistern remain operational points may be claimed. maintained in operation in compliance with the requirements of this BMP.

Lbmp T M D L - 11

Construct and maintain a structural BMP to reduce loadings of sediment and nutrients, including bioretention, detention basins, porous pavement, retention ponds, media filters and any composite treatment trains of multiple BMPs

A construction project installing a structural BMP must be completed prior to awarding of points. Any individual project will be awarded points scaled on the basis of the extent of the contributing area that the BMP will control. The permittee will document maintenance of the constructed BMP in subsequent years to continue to be awarded points.

By year five of this permit, at least two structural BMP projects will be constructed and maintained. Points will be awarded in the year construction was completed and subsequent points will be awarded in the subsequent vears after documentation of maintenance of the project.

4 points may be claimed for any year in which a structural BMP project is completed for a contributing area exceeding one acre. 3 points may be claimed for any year in which a structural project is completed for a contributing area under one acre. A bonus point may be awarded for a composite BMP project. 2 points may be awarded in subsequent

			years upon documentation of ongoing maintenance of the BMPs.
Lbmp T M D L - 12 Construct a stream bank stabilization project.	Install a minimum of 100 feet of bank stabilization at a site(s) with a history of erosion.	The installation of, the minimum 100 feet of bank stabilization must occur in the year points are claimed at a single site or at multiple sites. The sites may be on the same stream or on different streams.	3 points may be claimed for the year in which the required minimum amount of stream bank stabilization is installed, 2 points may be claimed for each subsequent year it remains in effect.

- 1. Documentation of compliance with the goal and implementation time schedule must be maintained on file to claim the associated points. Permittee is responsible for implementing adequate BMPs to comply with the TMDL BMP Implementation Requirements of this permit and be able to claim at least the required number of points in the calendar years as specified above. Extent of compliance, i.e., equal or exceed the required annual point total or failure to reach the required annual point total, must be reported in the Annual Report.
- 2. The permittee is not limited to implementation of the BMPs listed in the above table. Several other BMPs may be implemented, however, only implementation of the BMPs listed in the table may be documented and counted toward the required annual point total.

The permittee shall implement Best Management Practices (BMPs) to reduce to the Maximum Extent Practicable the discharge of the TMDL regulated pollutants from the MS4 to the watershed of the impaired stream(s) as listed below:

TMDL TABLE

Total Maximum Daily Loads, TMDLs, are established for waters found on the CWA Section 303d list of impaired waters. The purpose of the TMDL is to define the necessary and allowable pollutant load that may enter those impaired waters, so those waters attain a condition that fully supports all their designated uses. The TMDL then allocates portions of that allowable load among the likely point and non-point sources discharging the pollutant into the water or its watershed. Implementation of the TMDL by the NPDES and 319 programs brings about reductions in current loading from those sources through numeric goals or narrative actions to the allowable level allocated to each source.

TMDL Regulated Pollutant	Specific Impaired Stream(s) to Target
Bacteria	Dog Creek
Nutrients	Dog Creek
Sediment	Dog Creek

The required surface water monitoring locations* and their EDMR codes are identified as follows:

SURFACE WATER MONITORING LOCATIONS			
LOCAL SITE NAME	LOCAL ID.	LOCATION DESCRIPTION	KDHE EDMR CODE
Site #1	Upstream	Dog Creek 200 feet north of K-53 and 2,500 feet east of K-15.	DOG1001A6
Site #2	Downstream	Dog Creek at 140th Street bridge.	DOG2001B6

^{*} Note - Monitoring locations may change with KDHE approval.

Kansas Permit No.: M-AR64-SU01 Page 49 of 57

B. Monitoring Requirements

1. Storm Event Monitoring: The permittee shall implement a wet weather monitoring program with the intent to assess the impact of precipitation related discharges to the stream. Sampling and analysis will normally include, instream monitoring of the main stream(s) entering and leaving the Permit Area as identified in the TMDL Table. Alternately, in some cases main stream monitoring may not be appropriate as other sources of pollutants may be introduced by point or non-point discharges and tributaries to the listed main streams, which originate within or near the Permit Area, may be monitored at a single location to characterize the water quality draining from the permit area. The permittee shall implement this monitoring program to support adaptive stormwater management and the evaluation of SMP effectiveness in reducing the discharge of pollutants from the MS4. Monitoring for the parameters listed in the Parameters table shall be conducted as required for each storm event sampled which meets the criteria specified in this section.

The storm event monitoring data for TMDLs, as required in this PART II, may be used to assist in evaluating trends in water quality. This monitoring is not necessarily intended to demonstrate compliance with the requirements of this MS4 NPDES permit.

2. Additionally, other stream monitoring, monitoring of flow within the MS4, monitoring of discharges from MS4 outfalls, monitoring to detect or locate illicit discharges, and monitoring stormwater flow within structural BMPs may be completed at the permittee's discretion to assist in management and evaluation of the BMPs and the SMP. These additional monitoring results are not required to be reported to KDHE via the eDMR reporting process.

In addition to the storm event monitoring, the permittee may want to conduct dry weather monitoring, as appropriate, to determine the effectiveness of the six minimum control measures, detect illicit discharges, or to confirm baseline water quality data. These additional monitoring results are not required to be reported to KDHE via the eDMR reporting process.

C. Monitoring Frequency and Periods Criteria

- 1. Four storm events per year per monitoring site shall be monitored. Storm event shall mean a 24-hr rain or snow melt event of greater than or equal to 0.25 inches.
- 2. Monitoring shall normally be conducted in the spring (between March 1 and June 30) and summer (between July 1 and October 31) for the parameters as appropriate based upon the impairment. It is recommended two events be monitored in the spring and two events be monitored in the summer. However, it is most important four events be monitored in each calendar year and storm event monitoring can occur in any month.

Kansas Permit No.: M-AR64-SU01 Page 50 of 57

D. Parameters

TMDL Impairment	Parameter to be Monitored *	MRL **	Sample Type
Nutrients	Total Phosphorus as P (mg/l)	0.05 (mg/l)	Grab or Composite
Nutrients	Nitrate+Nitrite as N (mg/l)	0.10 (mg/l)	Grab or Composite
Nutrients	Total Kjeldahl Nitrogen (mg/l)	1 (mg/l)	Grab or Composite
Nutrients	Total Nitrogen (mg/l)		Calculate ***
Sediment	Total Suspended Solids (mg/l)	10 (mg/l)	Grab or Composite
Sediment	Turbidity (NTU)		Grab or Composite
Bacteria	E. coli (Col/100 ml or MPN)	10 (Col/100 ml or MPN)	Grab

* For a listed TMDL Regulated Pollutant in the TMDL Table, multiple parameters may be required to be monitored. In the case of Bacteria only one parameter needs to be monitored (E. coli). However, in the case of Sediment two parameters need to be monitored (Total Suspended Solids and Turbidity). In the case of Nutrients three parameters need to be monitored (Total Phosphorus, Nitrate+Nitrite as N, and, Total Kjeldahl Nitrogen). Additionally, one value needs to be calculated Total Nitrogen which equals the sum of Nitrate+Nitrite as N and Total Kjeldahl Nitrogen (the eDMR reporting process will calculate this value for the individual reporting the data).

Monitoring in impaired streams to test for TMDL pollutants, as listed in the TMDL Table does not necessarily require monitoring for all of the parameters listed in the Parameters table. For a stream, or its tributary, where monitoring is conducted, only the parameters associated with the listed TMDL Regulated Pollutant need to be monitored.

- ** Minimum Reportable Limit
- *** Total Nitrogen = Total Kjeldahl Nitrogen + Nitrate+Nitrite.

In addition, at the time of sampling, report the following:

- 1. Rainfall (last 24 hours) inches
- 2. Stream Flow CFS
- 3. Stream Depth from a standard Feet
- 4. Stream Level (rising, falling, steady)
- 5. Stream Velocity (rapid, normal, still [backwater])

Gauge Reading
Estimate/Reading
Estimate/Reading
Describe
Describe

For storm events, grab samples for instream monitoring are to be obtained within 4 hours of rising stages on streams. Monitoring of a storm event for the purpose of complying with the stormwater monitoring and reporting requirements of this permit is not allowed if there is not at least 24 hours between this sampling storm event and the end of the previous rainfall event. If composite sampling is conducted, samples are normally collected over the course of the hydrograph and flow-weighted to provide a representative composite sample for the storm event.

E. Adaptive Management

The monitoring program may be adapted to improve the effectiveness of the SMP or if supported by additional information. It may also be supplemented or supplanted with modeling approaches to meet monitoring plan objectives. Any modifications to the monitoring program are subject to KDHE approval.

Kansas Permit No.: M-AR64-SU01 Page 51 of 57

F. Documentation of Stream Monitoring Locations

The permittee, within 100 days following the effective date of this permit, shall provide KDHE maps illustrating the wet weather surface water monitoring locations and a table listing information associated with each monitoring location in a similar fashion as required by the annual reports. In some cases, KDHE has approved a rotational monitoring program where some monitoring locations are only monitored in certain years, if this is the case the table must list the years monitoring is required or alternately indicate all years. Information provided in the table shall be formatted similar to the following example:

Local Site Name	Farwell	
Local Site Identifier	C1	
Sample Location Description	On the east side of this bridge is a pedestrian walkway where a rope and bucket are lowered to the middle of the river to obtain a sample.	
KDHE EDMR Code if Known	Far2002C5	
Lat/Long Data - Decimal & Degr	ee Format	
Latitude	42.367056°	
Longitude	-71.218089°	
Years monitoring will be conducted	2019 and 2022 (Alternate notation is all years)	

EPA has promulgated a final rule requiring regulated entities to report DMR data electronically. Also, KAR 28-16-63 requires permittees to report NPDES data in a form required by KDHE. KDHE has developed electronic reporting tools to assist permittees in complying with the EPA electronic reporting rule and KAR 28-61-63. Unless a waiver has been approved by KDHE, permittees are required to submit reports electronically via the eDMR process.

The storm event monitoring data for TMDLs, as required in this PART II, is required to be reported to KDHE via the electronic DMR (eDMR) process. Additional monitoring of streams flowing within or near the Permit Area, monitoring industrial stormwater discharges (PART III), monitoring of discharges from MS4 outfalls, or discharges from areas with BMPs may be done at the permittee's discretion to assist in management and evaluation of the BMPs (process control/monitoring) and for compliance with the SMP and/or this permit. This additional monitoring is not required to be reported via the eDMR process.

PART III. MONITORING INDUSTRIAL STORMWATER DISCHARGES:

This PART III requirement is not applicable to Phase II permittees. No action is required at this time for Monitoring Industrial Stormwater Discharges.

PART IV. PERMIT COMPLIANCE ACTIVITIES AND SCHEDULES

A. Year 2019:

The required update to the stormwater management program (SMP) document, as required in PART I B. Updated Stormwater Management Program document, should be considered in 2019 and planning initiated for allocating time and effort to complete this task to update the SMP document prior to the submission deadline in 2021.

Permittees required to complete TMDL storm event monitoring of streams shall report results via the eDMR reporting process for all monitoring within a calendar year by no later than January 28 of the following year.

Within 100 days following the effective date of this permit the permittee must submit the required information regarding the wet weather surface water monitoring locations as addressed in PART II, B, 1 Monitoring Requirements.

The Annual Report for calendar year 2018 must be submitted to KDHE between January 1 and February 28, 2019.

B. Year 2020:

Any remaining tasks necessary to complete the update of the SMP should be completed in 2020.

Permittees required to complete TMDL storm event monitoring of streams shall report results via the eDMR reporting process for all monitoring within a calendar year by no later than January 28 of the following year.

The Annual Report for calendar year 2019 must be submitted to KDHE between January 1 and February 28, 2020.

C. Year 2021:

The updated SMP document must be submitted to KDHE with the 2020 Annual Report between January 1 and February 28, 2021.

The permittee must implement sufficient listed BMPs to achieve minimum point requirements for each year beginning in 2021.

Permittees required to complete TMDL storm event monitoring of streams shall report results via the eDMR reporting process for all monitoring within a calendar year by no later than January 28 of the following year.

The Annual Report for calendar year 2020 must be submitted to KDHE between January 1 and February 28, 2021.

D. Year 2022:

Permittees required to complete TMDL storm event monitoring of streams shall report results via the eDMR reporting process for all monitoring within a calendar year by no later than January 28 of the following year.

The permittee must implement sufficient listed BMPs to achieve minimum point requirements for each year.

The Annual Report for calendar year 2021 must be submitted to KDHE between January 1 and February 28, 2022.

Kansas Permit No.: M-AR64-SU01 Page 53 of 57

E. Year 2023

Permittees required to complete TMDL storm event monitoring of streams shall report results via the eDMR reporting process for all monitoring within a calendar year by no later than January 28 of the following year.

The permittee must implement sufficient listed BMPs to achieve minimum point requirements for each year. The point total requirements increase this year.

By February 28, 2023, provide a report (in PDF format) on effectiveness of source controls and structural BMPs to attenuate pollutant discharge and achieve the measurable goals. And if the TMDL Table in PART II lists TMDL Regulated Pollutants and the permittee is required to conduct surface water monitoring of specific impaired streams, this report must also summarize water quality data from in stream monitoring sites. This report must be submitted to KDHE along with the Annual Report for 2022.

The Annual Report for calendar year 2022 must be submitted to KDHE between January 1 and February 28, 2023.

F. Year 2024

Permittees required to complete TMDL storm event monitoring of streams shall report results via the eDMR reporting process for all monitoring within a calendar year by no later than January 28 of the following year.

The permittee must implement sufficient listed BMPs to achieve minimum point requirements for each year.

The Annual Report for calendar year 2023 must be submitted to KDHE between January 1 and February 28, 2024.

PART V. REPORTING

- A. The permittee shall submit a calendar year annual report to KDHE by February 28 of each year. The annual report shall be submitted to KDHE in the form specified by KDHE. Normally an annual report template (Basic Report) is posted on the KDHE website in the last three months of each year. The report template can be downloaded and completed. The completed annual report along with attachments or other documents which need to be submitted in association with the annual report shall all be submitted in PDF file formats to KDHE on a standard compact disk (CD) or digital versatile disk (DVD). The initial report under this permit is due February 28, 2020 for calendar year 2019. Once KDHE has implemented the KEIMS webbased system, all documents submitted will be required to be uploaded through the KEIMS program. KDHE will provide notification to the permittee when reporting via the KEIMS system is required. The annual report shall cover the activities during the previous calendar year and must include:
 - 1. Provide the status of compliance with permit conditions, an assessment of the appropriateness of the implemented Best Management Practices, progress towards achieving the statutory goal of reducing the discharge of pollutants to the maximum extent practicable (MEP), and the measurable goals with an indication of the progress toward meeting the goals for each of the six minimum control measures.

- 2. Provide results of information collected and analyzed, (for example test results, surveys, or public comments/input) during the annual reporting period. This may include monitoring data used to assess the success of best management practices with respect to reduction in pollutant discharge. Include an interpretation of the information which addresses success or failure of the portion of the program for which the information applies.
- 3. For Best Management Practices (BMPs), which are directed at reducing the discharge of TMDL regulated pollutants, provide the measurable goals of each BMP with an indication of the progress toward meeting the goals.
- 4. Provide results of information collected and analyzed, if any, during the annual reporting period, including monitoring data used to assess the success of the program at reducing the TMDL regulated pollutants.
- 5. Provide a summary of the stormwater activities that were scheduled to be undertaken during the previous calendar year and the status of these activities.
- 6. Provide a summary of the stormwater activities which are scheduled to be undertaken during the next calendar year (including an implementation schedule).
- 7. Provide a map showing changes in the permittee's Permit Area if the permit area has changed within the year.
- 8. Provide a description of significant changes in any of the BMPs.
- 9. Provide copies of any ordinances or resolutions which were updated in the last year and are associated with the SMP.
- 10. Provide a list of other parties (such as other municipalities or consultants), which are responsible for implementing any of the program areas of the Stormwater Management Program.
- B. Information and monitoring results gathered in compliance with PART II TOTAL MAXIMUM DAILY LOAD (TMDL) BEST MANAGEMENT PRACTICES AND SURFACE WATER MONITORING, must be reported in compliance with the eDMR reporting requirement as addressed in B. Monitoring Requirements, Frequency and Parameters.

STANDARD CONDITIONS FOR KANSAS WATER POLLUTION CONTROL AND NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM MS4 PERMITS

- 1. Representative Sampling and Monitoring Report Submittals:
 - A. Samples and measurements taken as required herein shall be representative of the quality of the monitored water. Test results shall be recorded for the day the samples were taken. All samples shall normally be taken at the locations designated by the permittee in the Stormwater Management Plan according to the requirements of this permit. In the event samples must be obtained from a location different than that designated in the Stormwater Management Plan the annual report shall indicate the change of location and provide the justification therefore.
 - B. Monitoring results shall be recorded and reported on forms acceptable to the Division and provided in the annual report. Signed and certified copies of the annual report prepared in accordance with KAR 28-16-59, and all other reports required herein, shall be sent by U.S. mail to:

Kansas Department of Health & Environment Bureau of Water-Municipal Programs Section 1000 SW Jackson Street, Suite 420 Topeka, KS 66612-1367

2. Definitions:

- A. A "grab sample" is an individual sample collected in less than 15 minutes. A "composite sample" is a combination of individual samples in which the volume of each individual sample is proportional to the flow, or the sample frequency is proportional to time.
- B. The terms "Director", "Division", and "Department" refer to the Director, Division of Environment, Kansas Department of Health and Environment, respectively.
- C. "Severe property damage" means substantial physical damage to property, damage to the treatment/control facilities which causes them to become inoperable, or substantial and permanent loss of natural resources which can reasonably be expected to occur in the absence of a diversion.
- 3. Duty to Mitigate: The permittee shall take all reasonable steps to minimize or prevent any damage to the environment or hazard to human health from any discharge in violation of this permit.
- 4. Test Procedures: All analyses required by this permit shall conform to the requirements of 40 CFR Part 136, unless otherwise specified, and shall be conducted in a laboratory accredited by the Department. For each measurement or sample, the permittee shall record the exact place, date, and time of measuring/sampling; the date and time of the analyses, the analytical techniques or methods used, minimum detection or reportable level, and the individual(s) who performed the measuring/sampling and analysis and, the results. If the permittee monitors any pollutant at the location(s) designated herein more frequently than required by this permit, using approved procedures, the results shall be included in the Monitoring Report form required in 1.B. above. Such increased frequencies shall also be indicated.
- 5. Change in Discharge: All stormwater discharges shall be in compliance with the conditions of the permit. Modification or expansion of the storm sewer system is allowed. All new storm sewer segments and outfalls constructed after the effective date of the permit, which are located within the permit area, are authorized under the permit and must comply with the permit conditions.
- 6. Proper Operations and Maintenance: The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the permittee to achieve compliance with the requirements of this permit and Kansas and Federal law.

Standard Conditions Page 55 of 57

7. Incident Reporting: The permittee shall report any unanticipated significant incidents which would be expected to result in non-compliance with the permit requirements within 24 hours from the time the permittee became aware of the incident. A written submission shall be provided within 5 days of the time the permittee became aware of the incident. The written submission shall contain a description of the noncompliance and its cause, the period of noncompliance, including exact dates and times; and if the noncompliance has not been corrected, the anticipated time it is expected to continue; and steps taken or planned to reduce, eliminate, and prevent recurrence of the noncompliance.

For an anticipated incident or any planned changes or activities in the permitted control/treatment facility that may result in noncompliance with the permit requirements, the permittee shall submit written notice, if possible, at least ten days before the date of the event.

- 8. Removed Substances: Solids, sludges, debris, or other pollutants removed in the course of control/treatment of stormwater shall be utilized or disposed of in a manner acceptable to the Division.
- 9. Right of Entry: The permittee shall allow authorized representatives of the Division of Environment or the Environmental Protection Agency upon the presentation of credentials, to enter upon the permittee's premises where a stormwater discharge or source is located, or in which are located any records required by this permit, and at reasonable times, to have access to and copy any records required by this permit, to inspect any facilities, monitoring equipment or monitoring method required in this permit, and to sample any stormwater discharges from or influents into the stormwater control/treatment facilities.
- 10. Transfer of Ownership: The permittee shall notify the succeeding owner or controlling person of the existence of this permit by certified letter, a copy of which shall be forwarded to the Division. The succeeding owner shall secure a new permit. This permit is not transferable to any person except after notice and approval by the Director. The Director may require modification or revocation and reissuance of the permit to change the name of the permittee and incorporate such other requirements as may be necessary.
- 11. Records Retention: Unless otherwise specified, all records and information resulting from the monitoring activities required by this permit, including all records of analyses and calibration and maintenance of instruments and recordings from continuous monitoring instruments, shall be retained for a minimum of 3 years, or longer if requested by the Division.
- 12. Availability of Records: Except for data determined to be confidential under 33 USC Section 1318, all reports prepared in accordance with the terms of this permit shall be available for public inspection at the offices of the Department. Treated and raw stormwater data shall not be considered confidential. Knowingly making any false statement on any such report or tampering with equipment to falsify data may result in the imposition of criminal penalties as provided for in 33 USC Section 1319 and KSA 65-170c.
- 13. Permit Modifications and Terminations: As provided by KAR 28-16-62, after notice and opportunity for a hearing, this permit may be modified, suspended or revoked or terminated in whole or in part during its term for cause as provided, but not limited to those set forth in KAR 28-16-62 and KAR 28-16-28b through g. The permittee shall furnish to the Director, within a reasonable amount of time, any information which the Director may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit or to determine compliance with this permit. The permittee shall also furnish upon request, copies of all records required to be kept by this permit. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition.
- 14. Administrative, Civil and Criminal Liability: The permittee shall comply with all requirements of this permit. Nothing in this permit shall be construed to relieve the permittee from administrative, civil or criminal penalties for noncompliance as provided for in KSA 65-161 et seq., and 33 USC Section 1319.
- 15. Oil and Hazardous Substance Liability: Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities or penalties to which the permittee is or may be subject to under 33 USC Section 1321 or KSA 65-164 et seq. A permittee shall promptly notify the Division by telephone upon discovering crude oil or any petroleum derivative in its storm sewer system or stormwater control/treatment facilities.

- 16. Property Rights: The issuance of this permit does not convey any property rights in either real or personal property, or any exclusive privileges, nor does it authorize any injury to private property or any invasion of personal rights nor any infringements of or violation of federal, state or local laws or regulations.
- 17. Severability: The provisions of this permit are severable. If any provision of this permit or any circumstance is held invalid, the application of such provision to other circumstances and the remainder of the permit shall not be affected thereby.
- 18. Removal from Service: The permittee shall inform the Division at least three months before any control/treatment unit, or any other part of the control/treatment facility permitted by this permit is to be removed from service and shall make arrangements acceptable to the Division to decommission the facility or part of the facility being removed from service such that the public health and waters of the state are protected.
- 19. Duty to Reapply: A permit holder wishing to continue any activity regulated by this permit after the expiration date, must apply for a new permit at least 180 days prior to expiration of the permit.

Standard Conditions Page 57 of 57